

## M17 FE str molded 6+PE PVC open end,5m



Part number	21 37 520 0703 050
Specification	M17 FE str molded 6+PE PVC open end,5m
HARTING eCatalogue	https://b2b.harting.com/21375200703050

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	System cabling
Series	Circular connectors M17
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	M17 Overmoulded Female Straight
Type of cable	Copper cable (round)
Version	
Cable length	5 m
Number of cores	7
Core structure	6x 0.5 mm <sup>2</sup> + 1 mm <sup>2</sup>
Technical characteristics	
Rated current	8 A
Rated voltage	300 V
Limiting temperature	-20 +80 °C
Degree of protection acc. to IEC 60529	IP65 IP67
Material properties	
Material (cable)	PVC
Colour (cable)	Black

Page 1 / 2 | Creation date 2022-04-26 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com



## Commercial data

Packaging size

Country of origin

1 China

European customs tariff number

eCl@ss

85444290 27060311 Assembled sensor actuator-line

Page 2 / 2 | Creation date 2022-04-26 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com