

Products	Coast™ Custom Cable	Applications	Resource Center	About Alpha Wire
Products	Coast™ Custom Cable	Applications	Resource Center	About Alpha Wire

Alpha Wire Home > Products > Tubing and Accessories > FIT® Wire Management > Braid > **2140**

Part #	Material	Shape	Size	Gauge Size	Current Rating	Applicable Specifications
2140	Tinned Copper	Oval	0.1875		38	

PART NO. 2140



This picture is representative only and may not match the specific configuration of the product listed on this page. Please refer to the product specifications for more information on this part number and its exact configuration.

[Share Page](#)

[Request a Sample](#)

[Check inventory](#)

[Add to Favorites](#)

[Download Spec](#)

(Ctrl+Click if PDF doesn't appear)

Construction	Applicable Specifications	Environmental	Other
1) Conductor			
a) Material		Tinned Copper, per ASTM-B33 and CID-A-A-5951	
b) Stranding		Solid	
c) Diameter		0.0063"	
2) Braid Data			
a) Nominal ID		3/16	
b) AWG of Ends		34	
c) Number of Carriers		24	
d) Nominal Percent Coverage		94	
e) Total Number of Ends		144	
f) Approx. Equiv. AWG		13	
g) Approx. Ampacity		38 Amps	
h) Federal Spec Number		N/A	

Alpha braid is an exceptional, low resistance way to create a point-to-point ground strap. In retrofit applications, braid is an ideal way to install additional shielding to your cable.

Try our newest addition to FIT family, [Brass Braid Sleeving!](#)

FIT Brass Braid is an attractive alternative to standard copper braid. It provides excellent EMI protection and generous expansion for flexibility during installation. It is ideal for medical, food + beverage, and semiconductor applications because it continuously *reduces bacterial contamination*, achieving 99.9% reduction within two hours of exposure.

Part #s: 2155, 2156, 2157, 2158

[Request a Sample](#)

[Download Brochure](#)

[Consult a Cable Expert](#)

Need a more unique construction? Different color code? Different color Jacket?

[Request a Custom Quote](#)

[Resources](#)

