

## Plug-in card block - SKBD 20/MT - 2202631

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in card block, Nominal current: 5 A, Number of positions: 20, Pitch: 5 mm, Connection method: Screw connection with tension sleeve, Contact surface: Tin



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 053376
Weight per Piece (excluding packing)	59.63 g
Custom tariff number	85369010
Country of origin	Poland

### Technical data

#### Dimensions

Length	23.6 mm
Height	18.4 mm
Pitch	5.00 mm

#### General

Range of articles	SKBD
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	5 A (applies to gold-plated contacts of the PCB)
Nominal voltage $U_N$	400 V
Nominal cross section	2.5 mm <sup>2</sup>
Stripping length	8 mm
Screw thread	M3

# Plug-in card block - SKBD 20/MT - 2202631

## Technical data

### General

Tightening torque, min	0.5 Nm
Tightening torque max	0.6 Nm
Number of positions	20

### Connection data

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section flexible min.	0.2 mm <sup>2</sup>
Conductor cross section flexible max.	1.5 mm <sup>2</sup>
Conductor cross section AWG min.	24
Conductor cross section AWG max.	14

### Standards and Regulations

Connection in acc. with standard	EN-VDE
	UL

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260710
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152
eCl@ss 9.0	27141152

### ETIM

ETIM 3.0	EC000446
ETIM 4.0	EC002642
ETIM 5.0	EC002780

### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

# Plug-in card block - SKBD 20/MT - 2202631

## Approvals

Approvals

---

Approvals

UL Recognized / EAC / EAC

---


Ex Approvals

---

Approvals submitted

---

## Approval details

UL Recognized 		
	B	D
mm <sup>2</sup> /AWG/kcmil	30-14	30-14
Nominal current I <sub>N</sub>	10 A	10 A
Nominal voltage U <sub>N</sub>	250 V	300 V

EAC

EAC

## Drawings

# Plug-in card block - SKBD 20/MT - 2202631

Dimensional drawing

