

## Data sheet



Item no.: 232-204/026-000  
 Product description: ANGLED FEMALE PLUG; 4 POLE; PIN SPACING 5 MM / 0.197 IN; WITH CODIG FINGERS; WITH INTEGRATED FIXING FLANGES; CONDUCTOR EXIT SAME DIRECTION AS LATCHES



Packing unit 100 pieces

Pin spacing from	5 mm
Pin spacing from	0,197 in
pole count	4
Cross section from [mm <sup>2</sup> ]	0,08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2,5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP®CONNECTION
Voltage CSA	300 V
Voltage UL	300 V
Current UL	15 A
Current CSA	15 A
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	14 A
Weight	7,65 g
Color	grey
No. of connection Points	4
No. of potentials	4
Height	19,9 mm
Height	0,783 in
Width	22,4 mm
Width	0,882 in
Depth	22,75 mm
Depth	0,896 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0,33 in

© WAGO Kontakttechnik GmbH & Co. KG  
 Specifications are subject to changes and errors may be expected