


Item no.: 232-407/026-000
 Product description: ANGLED FEMALE PLUG 7 POLE PIN SPACING 5.08 MM / 0.2 IN WITH CODING FINGERS WITH INTEGRATED FIXING FLANGES CONDUCTOR EXIT SAME DIRECTION AS LATCHES



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	13.225 g
Color	orange
No. of connection Points	7
No. of potentials	7
pole count	7
Height	19.9 mm
Height	0.783 in
Width	37.96 mm
Width	1.494 in
Depth	22.75 mm
Depth	0.896 in
Pin spacing from	5.08 mm
Pin spacing from	0.2 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV

Current intensity EN	14 A
Pollution degree	2
Measured voltage EN	630 V
Measured shock voltage	4 kV
Current intensity EN	14 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm²]	0.08 - 2.5 mm²
Wiring method	solid
Cross section [mm²]	0.08 - 2.5 mm²
Cross section [mm²]	0.25 - 1.5 mm²
Cross section [mm²]	0.25 - 2.5 mm²
Cross section [AWG]	28 - 12 AWG
Strip length from	8 mm
Strip length to	9 mm
Material group	I
xxx-xxx/034-000	Strain relief plate 30 mm



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
232-407/026-000	BV	11915/A0	400	16	2,5
232-407/026-000	CCA	5764	250	16	1x1
232-407/026-000	CSA	154112-1466354	300	15	22-12
232-407/026-000	KEMA	2083746.02	250	16	1x1
232-407/026-000	KR	HMB05880-EL003	250/400	12/16	2,5
232-407/026-000	UR	E45171	600	15	28-12
232-407/026-000	UR	E45172	300	15	22-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected