

Honeywell Sensing and Control

Home> Products > Thermostats > 2455RM> Product Page

- Order Product and Get Support
- U.S. Authorized
 Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request

2455RM 85010006



2455RM Series Phenolic Manual Reset Thermostats



My Links

Login to iCOM Login as Rep/AD Login as Guest Login to Digital University

Keyword Search

Search for product and support information.



- RoHS Product List
- Customer Feedback

Actual product appearance may vary.

Potential Applications

Cost effective Rivet sleeve construction Manually resetable

Description

Features

The 2455RM Series consists of a temperaturesensitive bimetal disc, electrically isolated from the switch, which actuates the normally closed contacts. The contacts open when the surface or ambient temperatures increase to the operating snap point of the calibrated disc. The circuit will stay open above room ambient temperature until the manual reset button is pressed. Response to temperature changes is extremely rapid due to the inherently low mass of the disc and the small size of the product.

HVAC

Power supplies

Office automation

Supporting Documentation

None Available

Product Specifications	
Functional Properties	Open on rise
Reset Type	Manual
Amperage	15 A/10 A
Voltage	120 Vac/250 Vac
Operating Temperature Range	0 °C to 150 °C [32 °F to 302 °F]
Environmental Exposure Range	- 18 °C to 177 °C [0 °F to 350 °F]
Open Temperature	83.3 °C [182 °F]
Close Temperature	Manual
Open Tolerance	5.6 °C [10 °F]
Dielectric Strength	MIL - STD - 202, Method 301; 2000 Vac 60 Hz - Terminal to Case
Insulation Resistance	MIL - STD - 202, Method 302; Cond. B - 500 MOhm - 500 Vdc applied
Contact Resistance	MIL - STD - 202, Method 307; 0.050 Ohm
Housing Material	Phenolic
Contact Material	Silver/nickel alloy
Approvals	UL, CSA, VDE
Mounting	B209 fixed bracket
Series Name	2455RM

Product Search
Part number search:
Use (*) to expand search
Specification Search

