



Plan view shielding front/rear side

Kit, for CompactPCI, for backplane mounting, for rear I/O, shielded

Catalog Number:24563-157

[Back To Product](#)

- Shielding typically 1GHz = 40dB, 2GHz = 30dB, assuming that the front is closed with shielded front panels
- Subrack with side panel type F ("flexible") for CompactPCI plug-in units with high insertion and withdrawal forces
- Horizontal rail rear for backplane mounting with insulation strip
- Installed load up to 11 kg
- Shielding typically 40 dB at 1 GHz, 30 dB at 2 GHz, assuming that the front is covered with shielded front panels
- For CompactPCI plug-in units to IEEE 1101.10
- europacPRO "flexible" version
- With and without rear I/O For rear I/O boards (depth 80 mm)



Products per Package:

1.0

Products per Package:

1.0

Other Views



[Change Item >](#)

CHANGING AN ITEM WILL UPDATE THE CATALOG NUMBER. THIS CAN AFFECT THE LIST PRICE AND SPECIFICATION OF THE ITEM.

Quantity

1

[Add Item to Project List +](#)

Kit, for CompactPCI, for backplane mounting, for rear I/O, shielded

Catalog Number 24563-157

Width HP 84.0

Depth D1 mm 175

Depth D3 mm 80

Description shielded (IEEE)

EXPLORE

- [About Us](#)
- [Services & Capabilities](#)
- [News and Events](#)
- [Strategic Partnerships](#)
- [Investor Relations](#)

CONTACT

- [Customer Service](#)
- [Find a Sales Office or Distributor](#)
- [Global Locations](#)
- [Product Compliance & Certifications](#)
- [Partner Login](#)

DOWNLOAD

- [Literature](#)
- [White Papers & Case Studies](#)
- [Videos & Mobile Apps](#)
- [Product Configurators](#)
- [Warranties](#)