

MTA 30 MF**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Due to the wide range of variants with output voltages of 5, 12, 24, and 48 V and extensive international approvals, they are suitable for use in many applications. The power range extends from 35 W to 350 W. The individual adaptability makes PRO-PM the right choice for many standard machines.

General ordering data

Version	Electronics housings, Mounting flange
Order No.	1251320000
Type	MTA 30 MF
GTIN (EAN)	4050118042702
Qty.	1 pc(s).

MTA 30 MF

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	10.5 mm	Height (inches)	0.413 inch
Width	30 mm	Width (inches)	1.181 inch
Length	97.3 mm	Length (inches)	3.831 inch
Weight	97 g	Net weight	97 g

General data

Weight	97 g
--------	------

Classifications

ETIM 6.0	EC002625	ETIM 7.0	EC002625
ETIM 8.0	EC002625	ECLASS 9.0	27-18-28-07
ECLASS 9.1	27-04-92-90	ECLASS 10.0	27-18-28-07
ECLASS 11.0	27-18-28-07		

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN_WSCAD
Catalogues	Catalogues in PDF-format
Brochures	