

Datasheet

Art.No. 25.163.0453.0

Printed circuit board terminal 8291 / 4 OB

PCB Terminal Block, 4-pole, without marking and insulation plate, pitch 5,08 mm, series: 8291/4 OB



Art.No.	25.163.0453.0
EAN	4015573176690
Order unit	50 pieces

Approvals



Technical data

General

Modular spacing	5.08 mm
Connection type	Screw connection
Soldering process	Wave soldering
Packaging	Carton
Number of poles	4
Conductor to circuit board	180°
Number of levels	1
Integrated test socket	Yes
Insulation plate	No
Retaining pins	No
Marking	No

Technical data

Nominal cross section	2.5 mm ²
Rated current	16 A
Overvoltage Category I	1000 V
Overvoltage Category II	690 V
Overvoltage Category III	250 V
Rated impulse voltage	4 kV
Wire strip length	6.5 mm

Connection Data

Minimum cross section solid	0.14 mm ²
-----------------------------	----------------------

Maximum cross section solid	4 mm ²
Minimum cross section fine stranded	0.14 mm ²
Maximum cross section fine stranded	2.5 mm ²
Wire strip length	6.5 mm

Technical Data UL/CSA

Cross section UL	22-12 AWG
Voltage UL	300 V
Current field wiring	20 A
Current factory wiring	30 A
Cross section CSA	22-12 AWG
Voltage CSA	300 V
Current CSA	25 A

Other

Type of insulation material	Thermoplastic
Colour	Grey
Height	15 mm
Length	21.17 mm
Depth	9.5 mm
Material attachment screw	Steel
Material contact base	E-Cu
Material contact surface	Sn

Classification

ECLASS 8.1	27440401
ETIM 6.0	EC002643
ETIM 5.0	EC002643
ETIM 4.0	EC002643



Drawings

Schnitt A-A
section A-A

Nichtergabe jeder Einzelzeichnung dieses Bauelements, Verwertung und Mitteilung eines Teils oder ganzer, sowie nach ausdrücklicher Genehmigung. Die Reproduktion, Vervielfältigung und Verbreitung dieses Dokuments ist ohne schriftliche Genehmigung der Wieland Electric AG ist ausdrücklich untersagt.

Gezeichnete Ausführung
10-polig
drawn version
10 poles

Weitere Daten siehe Katalog
further data see catalog

25.163.2453.F	8291/24 OB	24	116,84	121,92	122,77
25.163.2353.F	8291/23 OB	23	111,76	116,84	117,69
25.163.2253.F	8291/22 OB	22	106,68	111,76	112,61
25.163.2153.F	8291/21 OB	21	101,60	106,68	107,53
25.163.2053.F	8291/20 OB	20	96,52	101,60	102,45
25.163.1953.F	8291/19 OB	19	91,44	96,52	97,37
25.163.1853.F	8291/18 OB	18	86,36	91,44	92,29
25.163.1753.F	8291/17 OB	17	81,28	86,36	87,21
25.163.1653.F	8291/16 OB	16	76,20	81,28	82,13
25.163.1553.F	8291/15 OB	15	71,12	76,20	77,05
25.163.1453.F	8291/14 OB	14	66,04	71,12	71,97
25.163.1353.F	8291/13 OB	13	60,96	66,04	66,89
25.163.1253.F	8291/12 OB	12	55,88	60,96	61,81
25.163.1153.F	8291/11 OB	11	50,80	55,88	56,73
25.163.1053.F	8291/10 OB	10	45,72	50,80	51,65
25.163.0953.F	8291/ 9 OB	9	40,64	45,72	46,57
25.163.0853.F	8291/ 8 OB	8	35,56	40,64	41,49
25.163.0753.F	8291/ 7 OB	7	30,48	35,56	36,41
25.163.0653.F	8291/ 6 OB	6	25,40	30,48	31,33
25.163.0553.F	8291/ 5 OB	5	20,32	25,40	26,25
25.163.0453.F	8291/ 4 OB	4	15,24	20,32	21,17
25.163.0353.F	8291/ 3 OB	3	10,16	15,24	16,09
25.163.0253.F	8291/ 2 OB	2	5,08	10,16	11,01

.F	Farbe/ colour
.0	grau/grey
.1	schwarz/black
.7	grün/green
.9	orange

Teile - Nr. part - no.	Typ type	Polz. pole	T	L	G
25.163.0253.F	8291/ 2 OB	2	5,08	10,16	11,01

Information nach DIN 7167/Tolerance system acc. to DIN 7167.
(This DIN-standard describes the envelope principle. According to the envelope principle the deviations of form and parallelism are limited by the size tolerances).

Material: 2007
 Zeichnung Nr./Drawing No.: 25.163.0253.0 01K
 Index: 1

Wieland
Elektronische Verbindungen
LP_KLEMME
PCB terminal
Rastermaß 5,08 / pitch 5,08