

Item no.: 255-402  
 Product description: PCB TERMINAL STRIP; 2 SOLDER PINS / POLE; 2 POLE;  
 PIN SPACING 5/5.08 MM / 0.2 IN; WITH PUSH BOTTONS;  
 FRONT-ENTRY



Packing unit 400 4\*100 pieces

Product group	4 (Printed Circuit)
Pin spacing from	5 mm
Pin spacing up to	5,08 mm
Pin spacing from	0,197 in
Pin spacing up to	0,2 in
pole count	2
Cross section from [mm <sup>2</sup> ]	0,08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2,5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP®CONNECTION
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	16 A
Measured voltage EN	500 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	16 A
Weight	2,47 g
Color	grey
Wiring type	Front-entry



No. of potentials	2
Height	14,2 mm
Height	0,559 in
Width	12,9 mm
Width	0,508 in
Depth	18,3 mm
Depth	0,72 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0,22 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
255-402	ABS	04-HG469925-PDA	500/250	16	0,5-2,5
255-402	BBJ	B/12/697/03	250	16	0,5-2,5
255-402	BV	11915/A0	500/250	16	0,08-2,5
255-402	CCA	NL6248	250	24	0,08-2,5
255-402	CSA	18677-45	300/600	15/5	28-12
255-402	DNV	E7569	500/250	16	0,08-2,5
255-402	GL	17296-00HH	500/250	16	0,5-2,5
255-402	KEMA	2110204.02	250	16	0,5-2,5
255-402	RMR	11130002	250	16	0,5-2,5
255-402	UR	E45172	300	15	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected