

On the bottom menu bar, click **Page by Page** to access a page index or **Pages-at-a-Glance** to access a section index. View single pages in order by clicking **Previous** or **Next**. For improved print clarity, click **Page in PDF**. To **Print a PDF** be sure to select **Current Page** in your print monitor. Click **Email to a friend** to send a page to a third party. **Search** by 9 digit (54.003.7553) or 5-digit (54003) part number, series (WKC), or type of product (PCB connectors).

**PC board connectors
pluggable, spacings: 5.00/10.00 mm**

wiecon PCB

Rated cross section:
2.5 mm²

Rated current:
8 A

Connection range:
0.14 – 4.0 mm² solid/
0.14 – 2.5 mm² fine stranded

200 V/4 kV/3 – Overvoltage category III
250 V/4 kV/2 – Overvoltage category II
1000 V/4 kV/1 – Overvoltage category I

Spacing: 5.00 mm




Spacing: 10.00 mm




Type 8142

plug-in 90° to wire entry

Spacing: 5.00 mm



Spacing: 10.00 mm



Color: gray
Solder pin Ø 1.0 mm
Bore hole Ø 1.3 mm

Color: black
Solder pin Ø 1.3 mm
Bore hole Ø 1.6 mm

Terminal strip header

vertical mount

Rated voltages: VDE 0110 (spacing 5 mm)

UL ratings

CSA ratings

Approvals

No. 22 – 12 AWG

300 V

15 A

No. 22 – 12 AWG

300 V

15 A



Std pack	G	T	Poles	Part no. unmarked	Part no. marked	Part no. Color: gray	Part no. Color: black
Spacing: 5.00 mm							
100	10	5	2	25.602.2253.0	25.600.2253.0	25.530.0225.0	25.530.3225.0
100	15	10	3	25.602.2353.0	25.600.2353.0	25.530.0325.0	25.530.3325.0
50	20	15	4	25.602.2453.0	25.600.2453.0	25.530.0425.0	25.530.3425.0
50	25	20	5	25.602.2553.0	25.600.2553.0	25.530.0525.0	25.530.3525.0
50	30	25	6	25.602.2653.0	25.600.2653.0	25.530.0625.0	25.530.3625.0
50	35	30	7	25.602.2753.0	25.600.2753.0	25.530.0725.0	25.530.3725.0
50	40	35	8	25.602.2853.0	25.600.2853.0	25.530.0825.0	25.530.3825.0
50	45	40	9	25.602.2953.0	25.600.2953.0	25.530.0925.0	25.530.3925.0
50	50	45	10	25.602.3053.0	25.600.3053.0	25.530.1025.0	25.530.4025.0
50	55	50	11	25.602.3153.0	25.600.3153.0	25.530.1125.0	25.530.4125.0
50	60	55	12	25.602.3253.0	25.600.3253.0	25.530.1225.0	25.530.4225.0
50	65	60	13	25.602.3353.0	25.600.3353.0	25.530.1325.0	25.530.4325.0
50	70	65	14	25.602.3453.0	25.600.3453.0	25.530.1425.0	25.530.4425.0
50	75	70	15	25.602.3553.0	25.600.3553.0	25.530.1525.0	25.530.4525.0
50	80	75	16	25.602.3653.0	25.600.3653.0	25.530.1625.0	25.530.4625.0
17 to 24pole upon request							
Spacing: 10.00 mm				unmarked	marked		
50	20	10	2	25.603.1253.0	25.601.1253.0	25.530.6225.0	25.530.8225.0
50	30	20	3	25.603.1353.0	25.601.1353.0	25.530.6325.0	25.530.8325.0
50	40	30	4	25.603.1453.0	25.601.1453.0	25.530.6425.0	25.530.8425.0
50	50	40	5	25.603.1553.0	25.601.1553.0	25.530.6525.0	25.530.8525.0
50	60	50	6	25.603.1653.0	25.601.1653.0	25.530.6625.0	25.530.8625.0
50	70	60	7	25.603.1753.0	25.601.1753.0	25.530.6725.0	25.530.8725.0
50	80	70	8	25.603.1853.0	25.601.1853.0	25.530.6825.0	25.530.8825.0
9 to 12pole upon request							
Rated voltages: (spacing: 10.00 mm): VDE 0110 500 V/8 kV/3 – Overvoltage category III 800 V/8 kV/2 – Overvoltage category II 1000 V/8 kV/1 – Overvoltage category I				Material: PC board connectors Insulating housing: PC gray, UL 94-V-0 Clamping body: nickel-plated brass Clamping screws: zinc-plated steel Contact spring: tin-plated bronze Terminal strip header Insulating part: PA 66/6, glass-fibre reinforced gray or black, UL 94-V-0 Contact pin: tin-plated brass			

