



WIRING	
TIP	CENTER CONDUCTOR
SLEEVE	SHIELD

25 **A** **84** **X**
 1ST END - **ST-35** CABLE TYPE - **W-1000** 2ND END - **STRIP & TIN**

CABLE LENGTH
C - 18.00" ±0.50"
F - 3 FT ±1.00"
K - 6 FT ±1.00"
N - 10 FT ±1.00"
R - 15 FT ±1.00"

RoHS COMPLIANT

NOTES:

- MATERIALS:**
 PHONO PLUG
 PIN - COPPER ALLOY, NICKEL PLATED
 SLEEVE - COPPER ALLOY, BRIGHT TIN PLATED
 INSULATOR - PHENOLIC

OVERMOLD - THERMOPLASTIC

- THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					FINISH			MATERIAL	
					SPEC No.			SPEC No.	
					FIRST USED ON		SCALE 1.25:1		
B	25715	12-23-09	JEB	TJK	DATE DRAWN	BY	CHKD	APVD	
A	26206	01-29-07	JF	TJK	12-15-09	JEB	JEB	TJK	
							12-15-09		07-22-10
REV	ECO NUMBER	DATE	BY	APVD	NAME			PART No.	REV
REVISIONS					CABLE ASSEMBLY			25A_84X	B
					ST-35 TO S & T, RoHS				

DO NOT SCALE DRAWING

SolidWorks CAD File

