


Item no.: 264-210
 Product description: 4-CONDUCTOR TERMINAL STRIP WITH FIXING FLANGE FOR SCREW OR SIMILAR MOUNTING TYPES 3.2 MM Ø 10 POLE



Produkt kann von Bild abweichen / product may differ

Packing unit 25 pieces

RoHS compliant

Product group	9 (Std Chassis Mt Blocks)
pole count	10
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [AWG]	28 - 12 AWG
Connection method	CAGE CLAMP® CONNECTION
Number of strands	2
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	64 g
Color	gray
Wiring type	Front-entry
No. of connection Points	40
No. of potentials	10
Height	22 mm
Height	0.867 in
Width	116 mm

Width	4.567 in
Depth	32 mm
Depth	1.26 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
xxx-xxx/000-006	blue



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
264-210	ABS	04-HG476174/1-PDA	800	24	2,5
264-210	BV	07436/C0			0,08-2,5
264-210	CCA	NL6511	800	24	2,5
264-210	CSA	18677-23	600	20	26-12
264-210	DNV	E-9215	800	24	2,5
264-210	GL	17295-00HH	800	24	2,5
264-210	KEMA	2110272.04	800	24	2,5
264-210	KR	HMB05880-EL002	800	24	
264-210	LR	92/20242(E5)	800	24	2,5
264-210	PRS	TE/1718/880590/08	800		2,5
264-210	RMR	11130002	800	24	2,5
264-210	UR	E45172	300	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected