

Bus connector - IBS RL PLUG-LK/POF - 2731076

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The illustration shows various product versions

Connector for the fiber optic bus with polymer fiber cable and for the power supply with QUICKON connection method

Product Features

- Fiber optic or twisted pair version
- QUICKON or spring-cage connection technology
- Polymer fibers do not need to be polished

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	106.8 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Standards and Regulations

Connection in acc. with standard	CUL
----------------------------------	-----

Classifications

eCl@ss

eCl@ss 4.0	27250281
eCl@ss 4.1	27250281
eCl@ss 5.0	27259205
eCl@ss 5.1	27242692
eCl@ss 6.0	27242692
eCl@ss 7.0	27242692
eCl@ss 8.0	27249290

Bus connector - IBS RL PLUG-LK/POF - 2731076

Classifications

ETIM

ETIM 2.0	EC000313
ETIM 3.0	EC000313
ETIM 4.0	EC002584
ETIM 5.0	EC002584

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121311

Approvals

Approvals


Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals


Approvals submitted

Approval details

UL Recognized 	
mm ² /AWG/kcmil	22-18
Nominal current I _N	4 A
Nominal voltage U _N	250 V

Bus connector - IBS RL PLUG-LK/POF - 2731076

Approvals

cUL Recognized 	
mm ² /AWG/kcmil	22-18
Nominal current I _N	4 A
Nominal voltage U _N	250 V

EAC

cULus Recognized 
--