

Direct Mount Terminals

Feed Through






MK 2/12

MK 10/14

MK 3/12



MK 4/16



Available Options	Version	Type	Part No.	Type	Part No.	Type	Part No.	Type	Part No.
	2 pole					MK 3/2 KrG	0273820000		
	4 pole					MK 3/4 KrG	0274020000		
	6 pole					MK 3/6 KrG	0274220000		
	8 pole					MK 3/8 KrG	0274420000		
	10 pole					MK 3/10 KrG	0274620000		
	12 pole	MK 2/12 PA	0241260000			MK 3/12 KrG	0243520000		
	14 pole			MK 10/14 PA	0370160000				
	16 pole							MK 4/16 KrG	0244220000
	Melamine, KRG 2 pole (ATEX certified) ††					MK 3/2/E	7906110000		
	Melamine, KRG 3 pole (ATEX certified) ††					MK 3/3/E	7906120000		
	Melamine, KRG 4 pole (ATEX certified) ††					MK 3/4/E	7906130000		
	Melamine, KRG 5 pole (ATEX certified) ††					MK 3/5/E	7906140000		
	Melamine, KRG 6 pole (ATEX certified) ††					MK 3/6/E	7906150000		
	Melamine, KRG 7 pole (ATEX certified) ††					MK 3/7/E	7906160000		
	Melamine, KRG 8 pole (ATEX certified) ††					MK 3/8/E	7906170000		
	Melamine, KRG 9 pole (ATEX certified) ††					MK 3/9/E	7906180000		
	Melamine, KRG 10 pole (ATEX certified) ††					MK 3/10/E	7906190000		
	Melamine, KRG 11 pole (ATEX certified) ††					MK 3/11/E	7906200000		
	Melamine, KRG 12 pole (ATEX certified) ††					MK 3/12/E	7906210000		
Dimensions									
Width / Length / Height mm	mm (in.)	86/15/15 (3.39/.59/.59)		88.5/13.5/12 (3.48/.53/.47)		110/15/16.1 (4.33/.59/.63)		103/17/16 (4.0/.67/.67)	
Insulation stripping length mm	mm (in.)	5 (.20)		6 (.24)		5 (.20)		5 (.20)	
Technical Data									
Rated voltage / rated current / wire size	UL	300 V / 10 A / #24...12 AWG		150 V / 25 A / #22... 12 AWG		300 V / 20 A / #22...12 AWG		150 V / 15 A / #24... 12 AWG	
	CSA	300 V / 10 A / #24...12 AWG		300 V / 10 A / #24...12 AWG		300 V / 25 A / #22...12 AWG		150 V / 15 A / #22...12 AWG	
	VDE	60 VAC / 25 A / 2.5 mm ²		125 VAC / 25 A / 2.5 mm ²		380 VAC / 25 A / 2.5 mm ²		380 VAC / 20 A / 2.5 mm ²	
Torque	Nm (lb. in.)	0.5 (4.5)		.45 (4.0)		.9 (8.0)		0.5 (4.5)	
Clamping screw	M	2.5		2.5		2.5		2.5	
<p>The MK 10/14 can be mounted using glue or with M 3 x 12 screws through the terminal point chamber.</p>									
Tag Block / Plastic Rivet / Insulating Sleeve									
	Type	Part No.		Type	Part No.	Type	Part No.	Type	Part No.
	MF 2/12	0241760000							
	SN	0200100000							
Marking Strips									
	Print								
	Printed	BSTb 10/12	0245700000			BSTb 11/12	0245900000	BSTb 13/16	0262200000
		Bottom				BSTb 11/8	0290200000	Bottom	
		BSTb 10/12	0278500000			BSTb 11/6	0290000000	BSTb 13/16	0278700000
		Top				BSTb 11/4	0289800000	Top	
	Unprinted	BSTo 10/12	0245600000			BSTo 11/12	0245800000	BSTo 13/16	0262100000
						BSTo 11/8	0284700000		
						BSTo 11/6	0289500000		
						BSTo 11/4	0289300000		