

Connector/Adapter - BNC-DV 50 - 2805038

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



BNC connector, double-level, for mounting on NS 32 or NS 35/7.5, wave impedance: 50 Ohm

Product Features

- Can be labeled individually
- With isolated structure on the DIN rail
- For coaxial cables
- DIN rail-mountable and can be aligned

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 074548
Weight per Piece (excluding packing)	56.65 g
Custom tariff number	85366910
Country of origin	Poland

Technical data

Dimensions

Height	90 mm
Width	22 mm
Length	42.5 mm

Ambient conditions

Ambient temperature (operation)	125 °C
Degree of protection	IP20

General

Housing material	PA
Flammability rating according to UL 94	V2

Connector/Adapter - BNC-DV 50 - 2805038

Technical data

General

Color	gray
Mounting type	NS 35/7,5

Protective circuit

Frequency range	0 GHz ... 4 GHz
Standing wave ratio SWR in a 50 Ω system	< 1.15 (4 GHz)

Connection data

Connection method	BNC 50 Ω
-------------------	----------

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Classifications

eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141131
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27141190
eCl@ss 9.0	27141190

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002498
ETIM 5.0	EC002848

UNSPSC

UNSPSC 6.01	30211802
UNSPSC 7.0901	39121402
UNSPSC 11	39121410
UNSPSC 12.01	39121404
UNSPSC 13.2	39121404

