Terminal Strip



Compliant


RoHS




Specifications

Rated	: 10A 300V AC
Insulation Withstands Voltage	: AC 2000V/min.
Insulation Resistance	: $1000M\Omega$ or more at DC500V
Temperature Range	: -40°C to +120°C
Screw Torque Value	: 10Kg-cm
Wire Range AWG	: 14 - 18 STR
Insulator Body	: Plastic Nylon 66
Terminals	: Brass, Tin Plated 0.8t
Terminal Screws	: M3 Nickel Plated Steel

Diagram





Part Number Table

	Description	Part Number	
Millimetres	Terminal Strip, 8Pos, 10A	28-715	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the question of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. MCM is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

