

## Diode block - EMG 22-DIO 4E-1N5408 - 2952790

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Diode module, with 4 diodes, individually wired, diode type 1N 5408

### Why buy this product

- ✓ Electrical decoupling of messages in fault reporting systems
- ✓ Spark-suppression diodes for limiting surge voltages of inductive loads



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 084486
GTIN	4017918084486
Weight per Piece (excluding packing)	47.340 g
Custom tariff number	85411000
Country of origin	Germany

### Technical data

#### Dimensions

Width	22.5 mm
Height	75 mm
Depth	55 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

#### General

## Diode block - EMG 22-DIO 4E-1N5408 - 2952790

### Technical data

#### General

Diode type	1 N 5408
Peak reverse voltage per diode	1000 V
Reverse current per diode	10 µA
Conducting state voltage per diode	approx. 0.8 V
Conducting state current per diode	1.5 A (with single load)
	1 A (with simultaneous loads)
Standards/specifications	DIN EN 50178
Mounting position	any
Assembly instructions	In rows with zero spacing

#### Connection data

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section flexible min.	0.2 mm <sup>2</sup>
Conductor cross section flexible max.	2.5 mm <sup>2</sup>
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12
Stripping length	8 mm
Screw thread	M3
Connection method	Screw connection

#### Standards and Regulations

Standards/regulations	DIN EN 50178
Conformance	CE-compliant


#### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

### Drawings

# Diode block - EMG 22-DIO 4E-1N5408 - 2952790

Circuit diagram



## Classifications

### eCl@ss

eCl@ss 5.1	27371010
eCl@ss 6.0	27371010
eCl@ss 7.0	27371010
eCl@ss 8.0	27371010
eCl@ss 9.0	27371010

### ETIM

ETIM 4.0	EC000683
ETIM 5.0	EC000683
ETIM 6.0	EC000683

### UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	39121008
UNSPSC 11	39121008
UNSPSC 12.01	39121008
UNSPSC 13.2	32151504

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

## Diode block - EMG 22-DIO 4E-1N5408 - 2952790

### Approvals

#### Approval details

EAC		EAC-Zulassung
-----	---	---------------

### Accessories

#### Accessories

#### Marking material - EMG-GKS 12 - 2947035



Device marking label, width: 12 mm, area: 12 x 8 mm, e.g. for EML(10x7) R adhesive marking material