

Basic housing - UM-BEFE 35-1 - 2956660

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Base element with snap-on foot, for mounting on NS 32 or NS 35/7.5 DIN rail, without ribs, L = 35 mm



The illustration shows a combination of versions UM-SE-1, UM 16,5-1 BE, UM-BE 35-1, UM-BEFE 35-1, UM-SE-A 60-R and UM-A/U 73 CM

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	4 017918 085889
Weight per Piece (excluding packing)	22.0 g
Custom tariff number	85472000
Country of origin	Poland

Technical data

General

Conordi				
Housing material	Polyamide			
Color	green			
Ambient conditions				
Ambient temperature (operation)	-40 °C 105 °C			
Dimensions				
Width	35 mm			
Technical data				
Flammability rating according to UL 94	V0			
Standards and Regulations				
Flammability rating according to UL 94	V0			



Basic housing - UM-BEFE 35-1 - 2956660

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182701
eCl@ss 8.0	27182701

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC002779

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Δ	n	n	r	٦١.	12	ls
_	LJ	u	ı	JV	_	11.7

Approvals

UL Recognized

Ex Approvals


Approvals submitted

Approval details



Basic housing - UM-BEFE 35-1 - 2956660

Approvals



Phoenix Contact 2016 @ - all rights reserved http://www.phoenixcontact.com