

Interface module - UMK-32 MDSTB/MKKDS3/R - 2970196

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE module, with screw connection and COMBICON connector, coded, for mounting on NS 35/7.5 or NS 32, no. of positions 32



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 087685
Weight per Piece (excluding packing)	274.2 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Width	112.5 mm
Height	77 mm
Depth	58.5 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Max. perm. operating voltage	250 V AC/DC
Max. perm. current (per branch)	3 A
Number of positions	32
Mounting position	any

Interface module - UMK-32 MDSTB/MKKDS3/R - 2970196

Technical data

General

Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103

Connection data for connection 1

Connection name	PCB connection
Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Conductor cross section solid	0.2 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 14
Number of connections	1
Number of positions	32

Connection data for connection 2

Connection name	PCB connection
Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12
Number of connections	1
Number of positions	32

Standards and Regulations

Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313

Interface module - UMK-32 MDSTB/MKKDS3/R - 2970196

Classifications

eCl@ss

eCl@ss 5.1	27250313
eCl@ss 6.0	27242608
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152

ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC002780

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Drawings

Interface module - UMK-32 MDSTB/MKKDS3/R - 2970196

Circuit diagram

