Cat.6 Booted UTP Patch Cables

The range of Cat.6 patch cables are manufactured to high specification. Fully moulded in design they feature the use of 50 micron RJ45 plugs and fully approved stranded Cat.6 cable.

- Fully moulded backward compatible cables with both Cat.5 and Cat.5E networks & systems

- Manufactured using 50 micron gold RJ45 plugs & UL approved stranded cable

- Cable specification; 24 AWG ETL verified EIA/TIA-568A Cat.6 UTP with built-in centre spine which separates out each of the 4 twisted pairs

- Designed to give quality assured, fault-free data/voice transmission with high speed Gigabit networks

- Pin 1 to 1 wiring configuration, tested for purpose

Wiring Configuration

Pin 1	Colour	Pin 1
1	White/Orange	1
2	Orange/White	2
3	White/Green	3
4	Blue/White	4
5	White/Blue	5
6	Green/White	6
7	White/Brown	7
8	Brown/White	8

Length	Beige	Blue	Red	Green	Yellow	Black	White	Orange	Pink
0.5m	2996-0.5	2996-0.5B	2996-0.5R	2996-0.5G	2996-0.5Y	2996-0.5BK	2996-0.5W	2996-0.5RG	2996-0.5PK
1m	2996-1	2996-1B	2996-1R	2996-1G	2996-1Y	2996-1BK	2996-1W	2996-1RG	2996-1PK
1.5m	2996-1.5	2996-1.5B	2996-1.5R	2996-1.5G	2996-1.5Y	2996-1.5BK	2996-1.5W	2996-1.5RG	2996-1.5PK
2m	2996-2	2996-2B	2996-2R	2996-2G	2996-2Y	2996-2BK	2996-2W	2996-2RG	2996-2PK
3m	2996-3	2996-3B	2996-3R	2996-3G	2996-3Y	2996-2BK	2996-3W	2996-3RG	2996-3PK
5m	2996-5	2996-5B	2996-5R	2996-5G	2996-5Y	2996-5BK	2996-5W	2996-5RG	2996-5PK
8m	2996-8	2996-8B	2996-8R	2996-8G	2996-8Y	2996-8BK	2996-8W	2996-8RG	2996-8PK
10m	2996-10	2996-10B	2996-10R	2996-10G	2996-10Y	2996-10BK	2996-10W	2996-10RG	2996-10PK
15m	2996-15	2996-15B	2996-15R	2996-15G	2996-15Y	2996-15BK	2996-15W	2996-15RG	2996-15PK
30m	2996-30	2996-30B	2996-30R	2996-30G	2996-30Y	2996-30BK	2996-30W	2996-30RG	2996-30PK