

2A High Precision Tweezers



4 3/4" 120 mm Flat accurate round tips

2A.TA Titanium

General Notes

- Titanium Grade 1 (unalloyed titanium)
- engineering materials with extraordinary combination of properties: relatively low density (4.5 g/cm3), good mechanical properties and a very high melting point that allows the use at high temperatures (1600 °F, 870°C)
- good corrosion resistance at room temperature to air, marine and a variety of industrial environments
- good cold formability, high ductility
- fully non-magnetic
- generally it is used when in addition to the corros ion resistance, high strength-to-weight ratio is required
- bio-compatible (maintain cell integrity, no inflammatory response),
- typical applications include handling of components in cleaning/chemical processes also at high temperature, histology, biology, medicine, surgery.

Composition

| Component | W t.% | Component | Wt.% | Component | Wt.% |
|-----------|--------------|-----------|-------|-----------|--------|
| Ti | 99.5 | С | ≤0.1 | Fe | ≤0.2 |
| 0 | ≤0.18 | Ν | ≤0.03 | н | ≤0.015 |

Mechanical properties:

| State | annealed |
|-----------------------------|----------------|
| Density | 4.51 g/cm 3 |
| Hardness, Vickers | 122 HV |
| Tensile strength, ultimate: | 330 Mpa |
| Tensile strength, yield | 240 MPa |
| Elongation, break | 30% |
| Modulus of elasticity | 100 GPa |

Thermal properties

| Coef. of lin. therm expansion: | 9.2 E-67°C | 0°C-315°C |
|--------------------------------|-------------|-----------|
| Specific heat capacity | 0.52 J(g·K) | |
| Continuos use temperature: | 350°C | |
| Thermal conductivity: | 16W/(m·K) | |

Electrical properties

Resistivity

0.45E-4 Ohm.cm

© IDEAL-TEK SA Credits