




Home > Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

## 2TL256-3D



Actual product appearance may vary.

**TL Series Toggle Switch, 2 pole, 2 position, Screw terminal, Locking Lever**

### Features

Environmentproof sealing  
 1,2, and 4 pole circuitry  
 Standard and pull-to-unlock levers  
 2 and 3 position, maintained and momentary toggle action  
 Temperature range: -85° F to +160° F  
 Completely sealed switching chamber  
 Step-design case provides added space between terminals to help prevent shorting  
 UL recognized, CSA certified  
 CE approved

### Potential Applications

Industrial machinery and equipment  
 Military and commercial aviation  
 Construction equipment  
 Test instruments  
 Agricultural machinery  
 Process control  
 Medical instrumentation

### Description

MICRO SWITCH™ TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pull-to-unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

### Supporting Documentation

[Accessory: Seals](#)

[Accessory: Nuts](#)

[Engineering Drawing](#)

### Keyword Search

Search for product and support information.

All Sensing and Control

### Product Search

Part number search:

Use (\*) to expand search

Specification Search

Product Specifications									
Circuitry/Operating action	<table border="0"> <tr> <td style="text-align: center;"><b>Keyway Position</b></td> <td style="text-align: center;"><b>Opposite Keyway Position</b></td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> <tr> <td style="text-align: center;"><b>ON</b></td> <td style="text-align: center;"><b>ON</b></td> </tr> </table>	<b>Keyway Position</b>	<b>Opposite Keyway Position</b>					<b>ON</b>	<b>ON</b>
<b>Keyway Position</b>	<b>Opposite Keyway Position</b>								
<b>ON</b>	<b>ON</b>								
Product Type	MICRO SWITCH™ Toggle Switch								
Lever Lock	<p>Locked out of center position</p>								
Ampere/Voltage Range (Resistive Load)	0.75 A at 115 Vdc, 0.5 A at 250 Vdc, 0.5 A to 15 A at 0.5 Vac to 277 Vac, 0.5 A to 20 A at 0.5 Vdc to 28 Vdc								
Circuitry	DPDT								
Action	2 position								
Mounting	Bushing 15/32 in								
Termination	Screw								
Lever Type	Locking								
Comment	High force leverlock spring								
Availability	Global								
UNSPSC Code	30211908								
UNSPSC Commodity	30211908 Toggle switches								
Series Name	TL								