

End clamp - CLIPFIX 15 - 3022263

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Snap-on end bracket, to be snapped onto NS 15 DIN rail

Why buy this product

- ✓ Phoenix Contact has engineered its CLIPFIX end brackets to maintain a secure grip on the various DIN rail systems
- ✓ Design width of just 5.2 mm
- ✓ Parking option for bridges and plugs
- ✓ Large-surface labeling

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	50 STK
GTIN	 4 017918 976330
GTIN	4017918976330
Weight per Piece (excluding packing)	1.890 g
Custom tariff number	39269097
Country of origin	Poland

Technical data

Dimensions

Height	22.6 mm
Length	22 mm
Width	5.2 mm

General

End clamp - CLIPFIX 15 - 3022263

Technical data

General

Material	PA
Color	gray

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141135
eCl@ss 5.1	27141135
eCl@ss 6.0	27141135
eCl@ss 7.0	27141135
eCl@ss 8.0	27141135
eCl@ss 9.0	27141135

ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC001041
ETIM 4.0	EC001041
ETIM 5.0	EC001041
ETIM 6.0	EC001041

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121425

Accessories

Accessories

DIN rail

End clamp - CLIPFIX 15 - 3022263

Accessories

DIN rail, unperforated - NS 15 UNPERF 2000MM - 1401695



DIN rail, unperforated, Width: 15 mm, Height: 5 mm, In acc. with EN 60715: 2001, Material: Steel, Galvanized, passivated with a thick layer, Length: 2000 mm

DIN rail perforated - NS 15 PERF 2000MM - 1401682



DIN rail perforated, Width: 15 mm, Height: 5.5 mm, In acc. with EN 60715: 2001, Material: Steel, Galvanized, passivated with a thick layer, Length: 2000 mm

DIN rail perforated - NS 15 AL PERF 2000MM - 1401763



DIN rail perforated, Width: 15 mm, Height: 5.5 mm, In acc. with EN 60715: 2001, Material: Aluminum, uncoated, Length: 2000 mm

DIN rail perforated - NS 15 WH PERF 2000MM - 1204096



DIN rail perforated, Width: 15 mm, Height: 5.5 mm, In acc. with EN 60715: 2001, Material: Steel, Galvanized, white passivated, Length: 2000 mm
