

Representative

Catalog Number: 302-TB

 Product ID:
 7TAA106010R0001

 UPC Number:
 78621000302

Status: A

Metal-Clad and Armored Cable Fitting, Straight, Trade Size 1/8 Inch, Knockout Size 1/2 Inch, Cable Range 0.670 to 0.920 Inch, Steel with Zinc Plating

• For use with Armored Cable and Flexible Metal Conduit

| North American Specifications (UNSPSC) | |
|--|--|
| UNSPSC | 39121419 Flex connectors |
| IGCC | 4573 Flex connectors |
| Туре | Armored Cable/Flexible Metal Conduit Fittings |
| Special Features | Easy to Install with Double Grip Saddle, Connectors are Completely Salvageable |
| Application | To Connect and Effectively Bond Metal-Clad Ca- bles, Armored Cable, and Flexible Metal Conduit to a Box or Enclosure |
| Standard | UL E23018 |
| Size | 1/2 Inch |
| Conductor Range | 0.670 to 0.920 Inch |
| Material | Steel |
| Finish | Electro Zinc Plated |
| Color | Metallic |
| Insulation | No |

| European Specifications (ETIM) | |
|-------------------------------------|---|
| ETIM | EC001180 Screw connection for protective metallic |
| | hose |
| Nominal size in inch | 1/8 inch |
| Model | Straight |
| Revolving thread | N |
| Construction type | External thread |
| Connection type screw connection to | Other |
| housing | |
| Material housing | Steel |
| Surface protection | Zinc coated |
| Packaging | |
| Inner Quantity | 50 |
| Inner Dimensions (inches) | 4x5x8 |
| Outer Quantity | 100 |
| Outer Dimensions (inches) | 9.7x7.1x10.3 |
| Weight Uom | 12 lbs. per 100 |
| | · |

Documents / Support Tools

Technical Drawing / Data Sheet US Available on Website

Header

3D Model Available on Website

For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50

860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com