HOME THEATER



EPITOME® ROCKSTM COLLECTION

INTRODUCING EPITOME® ROCKSTM

GC Electronics adds Garden Rock speakers to the Epitome® line.

Epitome® Rocks™ are high fidelity speakers designed with high strength corrosion resistant fiberglass enclosures that simulate natural rocks. Each enclosure is waterproof and silicone sealed to provide years of listening enjoyment, regardless of weather conditions. Offered in seven models, they are perfect compliments to gardens, patios, pools, spas and walkways. They are also ideal for background music and public address systems at Hotels, Theme Parks, Civic Centres and Golf Courses. For individuality, the 30-3551 and 30-3552 can be used in pairs, as can the 30-3553, 30-3554 and 30-3555. The 30-3550 and 30-3556 should only be paired with themselves. 30-3550, 30-3551, 30-3552, 30-3554 and 30-3556 are "Forward Firing". 30-3553 and 30-3554 are "Omni-Directional".



Rock Garden Speakers for Outdoor and Public Address Use

Retail Part No.	Fig. No.	Dimensions: Width" (mm) x Height" (mm) x Depth" (mm)	Woofer Cone Inches (mm)	Voice Coil Inches (mm)	Power No. / Maximum	Magnet	Response Hertz	Efficiency	Dome Tweeter	Quantity
30-3550	1	9.65 (245) x 8.15 (207) x 9.06 (230)	5.25 (130)	1 (25)	30/60 Watt	10 oz.	120~20,000	86dB	.5" (13 mm)	1 Each
30-3551	2	12.52 (318) x 8.15 (207) x 9.06 (230)	6.5 (165)	1 (25)	45/100 Watt	10 oz.	85~20,000	85dB	.5" (13 mm)	1 Each
30-3555	2	14.09 (358) x 12 (305) x 10.87 (276)	8 (200)	1 (25)	55/120 Watt	15 oz.	75~20,000	85dB	.5" (13 mm)	1 Each
30-3552	3	11.81 (300) x 15 (381) x 10.28 (261)	6.5 (165)	1.5 (35)	45/100 Watt	10 oz.	85~20,000	86dB	2" (51 mm)	1 Each
30-3553	4	12.52 (318) x 14.76 (375) x 12.36 (314)	8 (200)	1.5 (35)	60/120 Watt	20 oz.	80~20,000	85dB	.5" (13 mm)	1 Each
30-3554	5	14.76 (375) x 19.69 (500) x 13.98 (355)	8 (200)	1.5 (35)	60/120 Watt	20 oz.	80~20,000	85dB	.5" (13 mm)	1 Each
30-3556	6	21.38 (543) x 13.58 (345) x 21.14 (537)	10 (250)	1.5 (35)	60/125 Watt	20 oz.	75~20,000	86dB	.5" (13 mm)	1 Each

All Rock Speakers Include: •Weather Resistant: Waterproof, -4°F/-20°C •Polystyrene Body •Impedance: 6 Ohms