

Catalog Number: 31013T

 Product ID:
 7TAH007890R0331

 UPC Number:
 78621080742

Status: Active

Locktite Copper Male Stud Connector for Conductor Range 4/0 to 300

• Fast, simple installation. Convenient pigtail is easy to take.

• Standard tapping shown in diagrams. Other tapping to meet specific requirements available on request.

North American Specifications (UNSPSC)	
UNSPSC	39121408 Mechanical connectors
IGCC	4541 Mechanical connectors
Brand Name	Blackburn
Туре	Locktite Connectors
Special Features	Fast, simple installation. Convenient pigtail is easy
	to take.
Standard	UL E9809
Material	Copper
Conductor Range (Main/Primary)	4/0 to 300

European Specifications (ETIM)	
ETIM	EC001051 Tube cable lug for copper conductors
Slender flange model	N
Insulated	N
Material	Copper

Packaging	
Inner Quantity	6
Inner Dimensions (inches)	4x4x3
Outer Quantity	30
Outer Dimensions (inches)	21.5x4.4x3.5
Weight Uom	72.22 lbs. per 100

For further technical assistance, please contact us...

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com ABB Installation Products Technical Support MS 3B-50

860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com