Thomas&Betts

T&B®

Armored Cable/Flexible Metal Conduit Fittings

T&B Catalog Number: 3117

UPC Number: 78621003117

Status: Active

Description:

1 in. Tite-Bite Insulated Connector, Malleable Iron-Electro Zinc Plated, Insulator-Thermoplastic.

Features

The tough lining of insulation and the Tite-Bite principles make these connectors a must when conductors are subject to conditions of vibration or strain.

Application

For use with Armored Cable and Flexible Metal Conduit.

To connect and effectively bond armored cable or flexible metal conduit to a box or an enclosure.

General

Trade Size (inches)	1
Material	Malleable Iron
Finish	Electro Zinc Plated

Dimension Information

Dimension A (inches)	2 3/8
Dimension B (inches)	1 3/4
Dimension C (inches)	1 1/8
Knockout Size (inches)	1
Cable Opening-Minimum (inches)	1.25
Cable Opening-Maximum (inches)	1.468

Specifications

3dmodel	Available on Website

Packaging

T&B Inner Pack	5
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	34.8 lbs. per 100

Certifications

RoHS Compliance	No

Certifications

File Nbr:

E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com