






**Terminal blocks**

to Type 219

-  **ASP046** page 53
-  **Type 213** page 102
-  **Type 214** page 102
-  **Type 249** page 100
-  **Type 250** page 100




**Accessories**

for **Type 219**  
**Coding set**  
 700024 page 180

**Type 219**


Header, centerline 5.08 mm / 0.200 inches, vertical mounting square contact pins 1 mm / 0.039 inches, open ends

**Technical Data**

	V / A	300 / 15
	V / A	300 / 15
		250 V / 4 kV / 10 A

Insulation co-ordination according to IEC 664-1			
Clearance and creepage distances	min. 4.08 mm		
Insulating material class	CTI 600		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Rated voltage	320	800	800
Rated test voltage	4	6	4
Protection category according to IEC 529	IP00		
Solder pin dimension	1.0 x 1.0 mm		
Recommended pc board hole dia.	Ø 1.5 mm		
Solder pin length	3.25 mm		
Pole size	2 - 24		
Color	black		

Dimensions in mm 1 mm = 0.0394 in.



$L = (\text{pole size} - 1) \times \text{centerline} + 5.08 \text{ mm} / 0.200 \text{ inches}$

**Part numbers (P/N)**

(informations: page 111)

Complete the part number by adding the pole size.

**Type 219**

centerline 5.08 mm / 0.200 inches

P/N 312191

	02	03	04	05	06	07	08
09	10	11	12	13	14	15	16
17	18	19	20	21	22	23	24

**Type 219**

centerline 10.16 mm / 0.400 inches

P/N 312192

	02	03	04	05	06	07	08
09	10	11	12				

- Standard pole sizes
- Available on demand. Minimum order quantity 5000 pieces per item.