




Home > Products > MICRO SWITCH™ Toggle Switches > NT > Product Page

### 31NT391-3-C08



Actual product appearance may vary.

**NT Series Toggle Switch, 1 pole, 2 position, Quick Connect terminal, Tab Lever**

#### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

#### Features

Completely sealed switching chamber  
 NEMA 3, 3R, 4, and 13  
 UL recognized, File E12252, Vol. 1, Section 44  
 CSA certified, File LR4442  
 CE approved

#### Potential Applications

Aerial lifts, scissor lifts, truck mounted tele-handlers, and cranes  
 Construction equipment  
 Agriculture equipment  
 Material-handling equipment  
 Factory-floor control units  
 Machine tool equipment manufacturers

#### Description

MICRO SWITCH™ NT Series toggle switches meet the need for a rugged, cost effective toggle switch. Quality construction features include a seal between the toggle lever and bushing, and between the cover and case. These switches can be used where panels are subject to splashes, hosedowns, or outdoor environments. The "Easy-Start" threaded bushing enables quick alignment of mounting nut to decrease the chance of cross threading. The panel stand-off with O-ring feature available on some listings, eliminates the need for behind-the-panel hardware, provides uniform panel height, and provides a panel to cover seal.

#### Supporting Documentation

[Accessory: Seals](#)

[Accessory: Nuts](#)

[Engineering Drawing](#)

| Product Specifications                |   |
|---------------------------------------|---|
| Circuitry/Operating action            | <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p><b>Keyway Position</b></p> <p>1 2 3<br/>ON</p> </div> <div style="text-align: center;"> <p><b>Opposite Keyway Position</b></p> <p>1 2 3<br/>ON</p> </div> </div> |
| Product Type                          | MICRO SWITCH™ Toggle Switch   |
| Ampere/Voltage Range (Resistive Load) | 0.5 A to 20 A at 0.5 Vdc to 28 Vdc, 0.5 A at 250 Vdc, 0.75 A at 115 Vdc, 0.5 A to 15 A at 0.5 Vac to 277 Vac  |
| Circuitry                             | SPDT  |
| Action                                | 2 position  |
| Mounting                              | Bushing 15/32 in  |
| Termination                           | Quick Connect   |
| Lever Type                            | Tab   |
| UL/CSA Rating Code                    | L191: 15 A - 125, 250, 277 Vac;<br>1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"   |
| Comment                               | Yellow  |
| Availability                          | Global  |
| UNSPSC Code                           | 30211908  |
| UNSPSC Commodity                      | 30211908 Toggle switches  |
| Series Name                           | NT  |

#### My Links

[Login to iCOM](#)  
[Login as Rep/AD](#)  
[Login as Guest](#)  
[Login to Digital University](#)

#### Keyword Search

Search for product and support information.

All Sensing and Control

#### Product Search

Part number search:

Use (\*) to expand search

[Specification Search](#)