Honeywell

Honeywell Sensing and Control

Home> Products > MICRO SWITCH[™] Toggle Switches > TW > Product Page

Order Product and Get Support

U.S. Authorized Distributors

- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

31TW2-205

TW Series Toggle Switch, 1 pole, 2 position, ? terminal, N/A Lever

Actual product appearance may vary.

Features

Save space and weight SPDT and DPDT circuitry Temperature range:-85? F to +160? F (-65? C to +71? C) Sealed bushing versions Choice of ? in. or 15/32 in. bushing Color tab available on 15/32 in. bushing UL recognized

Industrial machinery and equipment Military and commercial aviation Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

Potential Applications

Description

MICRO SWITCH[™] miniature toggle switches in two bushing sizes. Moldedin terminals are plated for soldering. Momentary and maintained circuitry closures available. Special on-on-on circuitries are also available. Pulłto-unlock levers prevent accidental operation.

Supporting Documenta	tion	
Accessory: Lever	Accessory: Seals	Accessory: Nuts
Sleeve	_	_
Engineering		
Drawing		

Product Specifications		
Circuitry/Operating action	Opposite Keyway Keyway Position Position 2 3 2 3 OFF ON	
Product Type	MICRO SWITCH [™] Toggle Switch	
Ampere/Voltage Range (Resistive Load)	0.01 A to 0.1 A at 0.5 Vac to 115 Vac,0.01 A to 0.1 A at 0.5 Vdc to 28 Vdc	
Circuitry	SPST	
Action	2 position	
Mounting	Bushing 15/32 in	
Termination	IWTS (16 - 20 Gage)	
Button Type	Special Design	
Comment	FAA- PMA approved, snap - on button	
Availability	Global	
UNSPSC Code	30211908	
UNSPSC Commodity	30211908 Toggle switches	
Series Name	TW	

