

321-50016



Article Number: 321-50016

Heat Shrink Tubing, 4FT Stick, Thick Wall Adhesive Lined, Up to 3.5:1, 3.25", 85/25 dia, Polyolefin, Black, 1/pkg



Download spec sheet

Base Data

Local Order Number	321-50016
Type	TREDUX HA47-48ST-85/25
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Tubing is 3.5:1, thick wall adhesive lined. • Toughness and weatherability is ideal for low and medium voltage power applications. • Available in 3.28' (1.0 m) lengths, multiple diameters and 1 color (black). • Conveniently packed in a display carton.
Product Description	TREDUX HA47 thick wall heat shrink tubing has a adhesive liner that provides good moisture sealing and weather protection suitable for insulation and protection of low and medium voltage power applications. HA47 is tough and the weatherability makes it suitable for exposed applications and underground cable joints. Polyolefin material is pre-cut into 3.28' (1.0m) sticks and stored in a convenient display box. RoHS approved and Halogen free.
Short Description	Heat Shrink Tubing, 4FT Stick, Thick Wall Adhesive Lined, Up to 3.5:1, 3.25", 85/25 dia, Polyolefin, Black, 1/pkg

Product Dimensions

Length L (Imperial)	4.0 ft
Length L (Metric)	1.0 m
Printable (Yes/No)	No
Shrink Ratio	up to 3.5:1
Tensile Strength (MPa)	14 MPa
Trade Size	3-1/4 "
Variant	Thick-Wall
Voltage Range	Low and Medium Voltage
Volume Resistance (Ohm cm)	10 ¹¹ Ω cm
Nominal Diameter (Imperial)	3-1/4 "
Nominal Diameter (Metric)	85 mm
Wall Thickness WT (Imperial)	0.169 "
Wall Thickness WT (Metric)	4.3 mm
Recovered Diameter d (metric)	25.4 mm
Recovered Diameter d (imperial)	1.0 "
Supplied Diameter D (imperial)	3.346 "
Supplied Diameter D (metric)	85.0 mm

Logistics and Packaging

Quantity Per	pieces
Package Quantity (Metric)	1 Pieces

Weight (Metric) 1.26 kg
Weight (imperial) 2.78

Material and Specifications

Material Polyolefin, cross-linked (PO-X)
Material Shortcut PO-X
Adhesive Hot melt adhesive
Dielectric Strength (Metric) 20 kV/mm
Elongation at break 400%
Flammability not flame retardant
Halogenfree Yes
Shrink Temperature +248 °F (+120 °C)
Operating Temperature -67°F to +230°F (-55°C to +110°C)
ROHS Compliant Yes
UL Listed (US) No
UL Recognized (US) No