




Applications on live equipment are subject to very special requirements. The focus is on absolute user safety and Wiha demonstrates this with a wealth of details.

The high quality blade insulation is moulded directly onto the blade and therefore guarantees safety when working on live equipment up to 1500 V DC or 1000 V AC. To maintain this safety, each screwdriver of the SoftFinish® electric series is individually tested in a water bath at 10.000 Volts according to DIN EN 60900.

The roll-off protection and the special handle geometry offer optimum handling and electrical safety, even in critical applications. Furthermore, the exclusive SoftFinish® handle shape allows maximum user comfort.

SoftFinish® electric Advantages:

- · Insulation moulded directly onto blade
- · Tested to the professional GS Standard
- Safety when working up to 1000 V AC and 1500 V DC
- Each screwdriver is individually tested in a water bath at 10.000 Volts according to DIN EN 60900 (IEC 900)
- Multi-component SoftFinish® handle provides maximum user comfort









Wiha SoftFinish®electric. The Safe & Comfortable Insulated VDE Screwdriver.

For TORX® Screws.







325 VDE TORX® Screwdriver.

Insulation up to 1000 V AC, GS-Mark.

Blade: High quality chrome-vanadium-molybdenum steel, through

hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® handle, multi-component with

roll-off protection.

Standards: Manufactured acc. to DIN EN 60900 (IEC 900), each tool

individually tested in a water bath at 10 000 Volts.

Application: For electrical applications up to 1000 V AC.

Order-No.		=-	==	-+	
03760 4	T5	60	164	23	10
03761 1	T6	60	164	23	10
037628	T7	60	164	23	10
00881 9	T8	60	164	23	10
00882 6	T9	60	164	23	10
008833	T10	60	164	23	10
00884 0	T15	80	191	30	10
00885 7	T20	80	191	30	10
00886 4	T25	80	198	36	10
00887 1	T27	100	218	36	10
00888 8	T30	100	218	36	10
00889 5	T40	150	274	41	5
03763 5	T45	150	274	41	5

For Hex Nuts.







322 VDE Nut Driver.

Insulation up to 1000 V AC, GS-Mark.

Blade: Chrome-vanadium steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® handle, multi-component with

roll-off protection.

Standards: DIN 7445.

Manufactured acc. to DIN EN 60900 (IEC 900), each tool

individually tested in a water bath at 10 000 Volts.

Application: For electrical applications up to 1000 V AC.

Order-No.	O	==	==	- ÷		
00853 6	4	125	236	30	10	namen and a large to the second
00855 0	5	125	236	30	10	831-499
00856 7	5.5	125	236	30	10	831-505
00857 4	6	125	236	30	10	831-517
00858 1	7	125	243	36	10	131-529
008598	8	125	243	36	10	831-530
00860 4	9	125	243	36	10	831-542
00861 1	10	125	243	36	10	831 - 554
008628	11	125	243	41	5	331-566
00863 5	12	125	243	41	5	331-578
00864 2	13	125	243	41	5	331-580
00865 9	14	125	243	41	5	
00866 6	15	125	243	41	5	
008673	16	125	243	41	5	
00868 0	17	125	243	41	5	



Wiha SetPoint Display - clever selling.

The Wiha SetPoint Display is a multi-talented aid for strong sales. The base unit holds up to 3 baskets for an impressive product presentation that makes maximum use of all the available area.

The display header fits all variants:

Mini: Upper (20 sets) and middle basket (28 sets), height 1.50 m. Midi: Middle (28 sets) and lower basket (36 sets), height 1.50 m.

Maxi: All baskets (84 sets), height 1.80 m.