Data Sheet

Within Series Adaptor 32_BNC-50-0-1/133_N



Description

Adaptor plug/plug

BNC plug (male) / BNC plug (male)

Interface standard

Series BNC - IEC 61169-8 MIL-STD-348A/301 CECC 22120

Technical Data

Electrical Data

 $\begin{array}{lll} \text{Impedance} & & 50 \ \Omega \\ \text{Interface frequency max.} & 4 \ \text{GHz} \\ \text{VSWR} & & \text{DC - 4 GHz} \\ \end{array}$

≤ 1.06 + 0.04 f (GHz)

Mechanical Data

Number of matings 500
Weight 0.0191 kg

Environmental Data

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS) compliant

Material Data

Interface - BNC plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Interface - BNC plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Related Documents

Catalogue drawing DCA-00013766

Ordering Information

Single package 32_BNC-50-0-1/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.