



Actual



Representative

**Catalog Number:** 3304  
**Product ID:** 7TAA106080R0003  
**UPC Number:** 78621003304  
**EAN Number:** 05414363134749  
**Status:** A

Sheathed Cable Fitting, Straight, Knockout Size 1 Inch, Two Screw Connector, Steel with Zinc Plating

### North American Specifications (UNSPSC)

UNSPSC	39121419 Flex connectors
IGCC	4573 Flex connectors
Brand Name	T&B
Type	Non-Metallic Sheathed Cable Conduit Fittings
Special Features	Rounded Cable Grip and Smooth Bushing Protect The Cable Sheath and Wire Insulation. Since Saddle is Threaded, Screws Do Not Travel or Extend Beyond The Connector Body As It is Clamped to The Cable. An Extra Lip on The Saddle Closes The Unused Part of The Connector Opening.
Application	To Connect Non-Metallic Sheathed Cable and Flexible Cord to a Box or an Enclosure.
Standard	UL E23013, CSA 2884
Size	1 Inch
Material	Steel
Finish	Electro Zinc Plated
Color	Metallic
Insulation	No

### European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	1 inch
Model	Straight
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Other
Material housing	Steel
Surface protection	Zinc coated

### Packaging

Inner Quantity	25
Inner Dimensions (inches)	4x5x6
Outer Quantity	100
Outer Dimensions (inches)	10.9x9.1x6.5
Weight Uom	14.88 lbs. per 100

### Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
-----------------------------------	----------------------

### Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289

