



C1 HAR-FLEX 26 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

C2 HAR-FLEX 26 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
25	AWG 30	25
26	AWG 30	26

HARTING P/N	REVISION	Cable length (L)
3315 243 006 0007	00	60 ± 3
3315 243 010 0007	02	100 ± 3
3315 243 020 0008	02	200 ± 3
3315 243 050 0009	02	500 ± 5
3315 243 027 0034	02	270 ± 5
3315 243 060 0034	00	600 ± 10
3315 243 100 0034	00	1000 ± 10
3315 243 012 0034	00	120 ± 3
3315 243 017 0034	00	170 ± 3
3315 244 065 0034	00	65 ± 3
3315 244 380 0034	00	380 ± 5

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE
HARTING P/N

	All rights reserved	Created by LIN Lin	Inspected by QINL Qin	Standardisation QINL Qin	Date 2020-03-30	State Final Release	Ref. \
	Department HCS - CN	Title Har-Flex 26 Pole,Dul-end,With SR,L=XX MM		Doc-Key / ECM-Nr. 100587128/UGD/000/H 500000169919		Rev. H	Sub. \
HARTING Customised Solutions D-32339 Espelkamp		Type TB	Number 33150003		Page 1/2		

