

33 Vinyl Electrical Tape

Data Sheet

Product Description

3M™ 33 Electrical Tape is a quality, general-purpose vinyl insulating tape. It has excellent resistance to; abrasion, moisture, alkalis, acid, copper corrosion and varying weather conditions (including sunlight). It is a polyvinyl chloride (PVC) tape that has a high dielectric strength, is flame-retardant and conformable, and provides excellent mechanical protection with minimum bulk. It is a UL Listed “Insulating Tape”.

- UL Listed; UL 510 Standard “Insulating Tape” (product category OANZ), File E129200
- Polyvinyl chloride (PVC) backing
- Pressure-sensitive rubber based adhesive
- Inhibits corrosion of electrical conductor
- Compatible with solid dielectric cable insulation

Applications

- Primary electrical insulation for all wire and cable joints rated up to 600V
- Protective jacketing for high voltage cable joints and repairs
- Harnessing of wire and cables
- For indoor and outdoor applications
- For above or below grade applications

Typical Data/Physical Properties

Temperature Rating	
UL510	80°C (176°F)
Flammability (Maximum)	
UL510	Pass
ASTM D1000	4 sec.
Dielectric Strength	
ASTM D1000	
Standard Condition	>5.6kV/mm
High Humidity	0% of Standard
Insulation Resistance	
ASTM D1000	>10 ⁶ Megohms
Thickness	
ASTM D1000	0.178mm
Elongation	
ASTM D1000	200%

Breaking Strength

ASTM D1000
22°C (72°F) 30N/10mm

Adhesion

ASTM D1000
To Steel 8.33N/mm
To Backing 7.63N/mm

Flagging

ASTM D1000 <2.5mm

Telescoping

24 Hours @ 50°C (120°F) <2.5mm

Note: These are typical values and should not be used for specification purposes.

Installation Techniques

The tape shall be applied in half-lapped layers with sufficient tension to conform and produce a uniform covering. In most applications, this tension will reduce the tape’s width. On pigtail joins, the tape should be wrapped beyond the end of the wires and then folded back, leaving a protective cushion to resist cut-through. Always wrap the tape up-hill, taping from a smaller diameter surface to a larger diameter surface. Apply the tape with no tension on the last wrap to prevent flagging.

Specifications

The tape is based on polyvinyl chloride (PVC) and/or its copolymers and has a rubber-based, pressure-sensitive adhesive. The tape shall be 0.178mm thick, and be UL Listed and marked per UL Standard 510 as “Flame Retardant and Weather Resistant”. The tape must be applicable at temperatures ranging from 0°C (32°F) through 38° (100°F) without loss of physical properties. The tape shall be classified for use in both indoor and outdoor environments. The tape shall be compatible with synthetic cable insulations, jackets and jointing compounds.

The tape will remain stable and will not telescope more than 2.5mm when maintained at temperatures below 50°C (120°F).

33 Vinyl Electrical Tape

Data Sheet

Engineering/Architectural Specification

Primary electrical insulation (branch wiring in wet or dry locations). All joints for 600 volt wire and rated 80°C (176°F) and below shall be insulated with a minimum of two half-lapped layers of 3M 33 Vinyl Electrical Tape. All connectors having irregular surfaces shall be padded with Scotchfil™ Electrical Insulation Putty or Scotch 130C Rubber Splicing Tape prior to insulating with 3M 33 Vinyl Electrical Tape.

Mechanical protection (outer jacketing). All rubber and thermoplastic insulating high voltage power cable tape joints and repairs shall be overwrapped with at least two half-lapped layers of 3M 33 Vinyl Electrical Tape.

Shelf Life

3M 33 vinyl electrical tape has a 5-year shelf life (from date of manufacture) when stored under the following recommended storage conditions. Store behind present stock in a clean dry place at a temperature of 21°C (70°F) and 40-50% relative humidity. Good stock rotation is recommended.

Availability

3M 33 Vinyl Electrical Tape is available from your local 3M authorised distributor in the following standard roll sizes:

12mm x 33M
19mm x 33M
25mm x 33M
38mm x 33M
50mm x 33M

Other lengths and widths are available by special request.

Important Notice

Technical information provided by 3M is based on experience and/or tests believed to be reliable, but their accuracy is not guaranteed and the results may not be relevant to every user's application. For this reason 3M does not accept responsibility or liability, direct or consequential, arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence. All questions of liability relating to 3M products are governed by the seller's terms of sale subject where applicable to the prevailing law. If any goods supplied or processed by or on behalf of 3M prove on inspection to be defective in material or workmanship, 3M will (at its option) replace the same or refund to the Buyer the price paid for the goods or services. Except as set out above, all warranties and conditions, whether express or implied, statutory or otherwise are excluded to the fullest extent permissible at law.

3M, Scotchfil and Scotch are trademarks of the 3M Company. Printed in the UK.
© 3M United Kingdom PLC, 2004.

Electrical Markets Division

3M United Kingdom PLC
Sales Office
PO Box 393
Bedford MK41 0YE
Telephone: 0870 609 4639
Fax: 01234 229 433

3M Ireland Ltd
Sales Office
The Iveagh Building, The Park,
Carrickmines, Dublin 18, Ireland
Telephone: (01) 800 812 732
Fax: 353 1 280 3509

3M United Kingdom PLC
Head Office
3M Centre, Cain Road
Bracknell, Berkshire RG12 8HT
Telephone: 01344 858 000
Fax: 01344 858 758