

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0340620038](#)  
**Status:** **Active**  
**Overview:**  
**Description:** MX150 Cable-Sealed Female Connector Assembly, Single Row, 2 Circuits, Keying Option C, with Clipslot, with Connector Position Assurance, Black

**General**

Product Family	Crimp Housings
Series	<a href="#">34062</a>
Application	Power, Wire-to-Wire
Comments	With Connector Position Assurance (CPA)
More Detailed Tech Information	<a href="http://uscar.org/guest/teams/10/Electrical-Wiring-Component-Applications-Partnership">http://uscar.org/guest/teams/10/Electrical-Wiring-Component-Applications-Partnership</a>
Overview	<a href="#">mx150_sealed_connector_system</a>
Product Name	MX150
UPC	884982142213

**Physical**

Circuits (maximum)	2
Color - Resin	Black
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	Nylon
Net Weight	5.690/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	5.00mm
Pitch - Termination Interface	5.00mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +125°C

**Solder Process Data**

Lead-freeProcess Capability	N/A
-----------------------------	-----

**Material Info**

**Reference - Drawing Numbers**

Application Specification	340620000-AS-CH-000, AS-34062-000-001
Packaging Specification	PK-30907-879-001
Product Specification	PS-34062-000-001
Sales Drawing	SD-34062-002-000, SD-34062-004-001
Test Summary	TS-34062-992-001

**EU ELV**  
**Compliant**

**EU RoHS** **China RoHS**  
**Compliant**

**REACH SVHC**  
Not Contained Per -  
D(2020)9139-DC (19  
Jan 2021)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS	Green Image
ELV	Compliant
RoHS Phthalates	Not Contained

**Search Parts in this Series**

[34062](#) Series

**Mates With**

MX150 Cable-Sealed Male Connector  
[34675](#)

**Use With**

Tin (Sn) Cable Seal Female Terminal [34083](#)  
<br>Silver (Ag) and Gold (Au) Cable Seal  
Female Terminal [34081](#)