



**Product:** [3612](#) 

CAT6+ Horizontal, 4pr, UTP, PVC Jkt, CMR

## Product Description

CAT6+ (400MHz), 4-Pair, U/UTP-unshielded, Riser-CMR, Premise Horizontal cable, 23 AWG solid bare copper conductors, polyolefin insulation, patented X-spline, ripcord, PVC jacket

## Technical Specifications

### Product Overview

Suitable Applications:	Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments
------------------------	--

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4

Conductor Count:	8
Total Number of Pairs:	4

#### Insulation

Material	
Polyolefin	
Bonded-Pair:	N/A

#### Color Chart

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord	Separator Material
PVC - Polyvinyl Chloride	0.231 in	0.017 in	Yes	Patented X-Spline Center Member

### Electrical Characteristics

#### Conductor DCR

Max. Conductor DCR	Max. DCR Unbalance
77 Ohm/km	3 %

#### Capacitance

Max. Capacitance Unbalance	Nom. Mutual Capacitance
330 pF/100m	15.5 pF/ft

#### Delay

Frequency [MHz]	Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]	Typical Delay Skew
100 MHz	537.6 ns/100m	35 ns/100m	70 %	35 ns/100m

## High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)
1 MHz	2.0 dB/100m	84.3 dB	82.3 dB	80.3 dB	80.3 dB	76.8 dB	73.8 dB	20.0 dB	100 ± 15
4 MHz	3.7 dB/100m	75.3 dB	73.3 dB	69.5 dB	69.5 dB	64.8 dB	61.8 dB	23.6 dB	100 ± 15
8 MHz	5.3 dB/100m	70.8 dB	68.8 dB	63.5 dB	63.5 dB	58.7 dB	55.7 dB	25.3 dB	100 ± 15
10 MHz	5.9 dB/100m	69.3 dB	67.3 dB	61.4 dB	61.4 dB	56.8 dB	53.8 dB	26.0 dB	100 ± 15
16 MHz	7.4 dB/100m	66.2 dB	64.2 dB	56.8 dB	56.8 dB	52.7 dB	49.7 dB	26.0 dB	100 ± 15
20 MHz	8.3 dB/100m	64.8 dB	62.8 dB	54.4 dB	54.4 dB	50.8 dB	47.8 dB	26.0 dB	100 ± 15
25 MHz	9.4 dB/100m	63.3 dB	61.3 dB	52.0 dB	52.0 dB	48.8 dB	45.8 dB	25.5 dB	100 ± 15
31.25 MHz	10.5 dB/100m	61.9 dB	59.9 dB	49.4 dB	49.4 dB	46.9 dB	43.9 dB	25.0 dB	100 ± 15
62.5 MHz	15.1 dB/100m	57.4 dB	55.4 dB	40.3 dB	40.3 dB	40.9 dB	37.9 dB	23.5 dB	100 ± 15
100 MHz	19.3 dB/100m	54.3 dB	52.3 dB	33.0 dB	33.0 dB	36.8 dB	33.8 dB	22.5 dB	100 ± 15
155 MHz	24.5 dB/100m	51.4 dB	49.4 dB	24.9 dB	24.9 dB	33.0 dB	30.0 dB	21.6 dB	100 ± 22
200 MHz	28.2 dB/100m	49.8 dB	47.8 dB	19.6 dB	19.6 dB	30.8 dB	27.8 dB	21.0 dB	100 ± 22
250 MHz	31.8 dB/100m	48.3 dB	46.3 dB	14.5 dB	14.5 dB	28.8 dB	25.8 dB	20.5 dB	100 ± 32
300 MHz	35.2 dB/100m	47.1 dB	45.1 dB	9.9 dB	9.9 dB	27.3 dB	24.3 dB	20.1 dB	100 ± 32
350 MHz	38.4 dB/100m	46.1 dB	44.1 dB	5.7 dB	5.7 dB	25.9 dB	22.9 dB	19.8 dB	100 ± 32
400 MHz	41.5 dB/100m	45.3 dB	43.3 dB	1.8 dB	1.8 dB	24.8 dB	21.8 dB	19.5 dB	100 ± 32
450 MHz	44.3 dB/100m	44.5 dB	42.5 dB			23.7 dB	20.7 dB	19.2 dB	100 ± 32
500 MHz	47.1 dB/100m	43.8 dB	41.8 dB			22.8 dB	19.8 dB	19.0 dB	100 ± 32
550 MHz	49.7 dB/100m	43.2 dB	41.2 dB			22.0 dB	19.0 dB	18.8 dB	100 ± 32
600 MHz	52.3 dB/100m	42.6 dB	40.6 dB			21.2 dB	18.2 dB	18.7 dB	100 ± 32
650 MHz	54.8 dB/100m	42.1 dB	40.1 dB			20.5 dB	17.5 dB	18.5 dB	100 ± 32

Segregation class according EN50174-2:

a

## Voltage

**UL Voltage Rating**

300 V RMS

## Temperature Range

Installation Temp Range:	0°C To +50°C
UL Temp Rating:	75°C
Storage Temp Range:	-20°C To +75°C
Operating Temp Range:	-20°C To +75°C

## Mechanical Characteristics

Bulk Cable Weight:	25 lbs/1000ft
Max Recommended Pulling Tension:	25 lbs
Min Bend Radius During Installation:	2.5 in
Min Bend Radius/Minor Axis:	1.0 in

## Standards

NEC Articles:	800
NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMR
ISO/IEC Compliance:	11801 ed 2.2 (2011) Class E
CPR Euroclass:	Eca
Data Category:	Category 6
ANSI Compliance:	S-116-732-2013 Category 6, ANSI/NEMA WC-66 Category 6
Telecommunications Standards:	ANSI/TIA-568.2-D Category 6
IEEE Specification:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
Third Party Performance Verification:	Category 6

## Applicable Environmental and Other Programs

Environmental Space:	Riser
EU Directive 2000/53/EC (ELV):	Yes

EU Directive 2002/95/EC (RoHS):	Yes
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
EU REACH SVHC Compliance (yyyy-mm-dd):	2017-07-10
EU RoHS Compliance Date (yyyy-mm-dd):	2009-04-03
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	No
Suitability - Oil Resistance:	No
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

## Flammability, LSOH, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL 1666 Riser
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	3613

## Part Number

### Variants

Item #	Color	Putup Type	Length	UPC
3612 0101000	Black	Reel	1,000 ft	612825145707
3612 010A1000	Black	Reel-in-Box	1,000 ft	612825145684
3612 010U1000	Black	UnReel	1,000 ft	612825145691
3612 0061000	Blue	Reel	1,000 ft	612825145585
3612 006A1000	Blue	Reel-in-Box	1,000 ft	612825145561
3612 006U1000	Blue	UnReel	1,000 ft	612825145578
3612 0062500	Blue	Reel	2,500 ft	612825145592
3612 0081000	Gray	Reel	1,000 ft	612825145639
3612 008A1000	Gray	Reel-in-Box	1,000 ft	612825335061
3612 008U1000	Gray	UnReel	1,000 ft	612825145622
3612 0051000	Green	Reel	1,000 ft	612825145554
3612 005A1000	Green	Reel-in-Box	1,000 ft	612825145530
3612 005U1000	Green	UnReel	1,000 ft	612825145547
3612 003A1000	Orange	Reel-in-Box	1,000 ft	612825145479
3612 003U1000	Orange	UnReel	1,000 ft	612825145486
3612 007A1000	Purple	Reel-in-Box	1,000 ft	612825145608
3612 007U1000	Purple	UnReel	1,000 ft	612825145615
3612 0091000	White	Reel	1,000 ft	612825145660
3612 009A1000	White	Reel-in-Box	1,000 ft	612825145646
3612 009U1000	White	UnReel	1,000 ft	612825145653
3612 0092500	White	Reel	2,500 ft	612825145677

3612 0041000	Yellow	Reel	1,000 ft	612825145516
3612 004A1000	Yellow	Reel-in-Box	1,000 ft	612825145493
3612 004U1000	Yellow	UnReel	1,000 ft	612825145509
3612 0042500	Yellow	Reel	2,500 ft	612825145523

Footnote:	C - CRATE REEL PUT-UP.
Patent:	<a href="https://www.belden.com/resources/patents">https://www.belden.com/resources/patents</a>

## Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Values above 400 MHz are for Engineering Information Only. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0.
--------	--

## History

Update and Revision:	Revision Number: 0.386 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.