



Fluke 333 Clamp Meter

The results you need, faster and more conveniently.

[Check price and availability](#)

Find out which of the new Fluke clamp meters is perfect for you.

[Clamp Meter Conversion Guide >](#)



[Overview](#) [Features](#) [Specifications](#) [Models and Accessories](#) [Knowledge and Information](#)

Specifications	
Diameter of measurable conductor	0.12" or 30.5 mm max
Operating temperature	-14 to 122°F (-10 to 50°C)
Storage Temperature	-40 to 140°F (-40 to 60°C)
Operating Humidity	< 90% @ <30 °C, < 75% @ 30 to 55°C
Operating Altitude	0 to 2500 m
IP Rating	IP 40
Size	240 x 80 x 44 mm, (9.375 x 3.125 x 1.625 in.)
Weight	310G, (11 oz.)
Vibration	Random 2 g, 5 to 500 Hz
Shock	1 meter drop test (except the jaw)
EMI/RFI	Meets EN61326-1
Temperature Coefficient	0.01% °C (<18? or > 28?)
Power, battery life	(2) AA 1.5 V Alkaline, IEC 1010-2-031, 150 hours typical Automatic low battery indicator
Warranty	Three years for electronics One year for cable and clamp assembly

[Clamp Meter](#) | [Current Meters](#) | [DC Clamp Meters](#) | [HVAC Clamp Meter](#)

Search Fluke

Resources Products



Find Resources

Select

Clamp Meter Videos

- [Fluke 381 with Remote Display \(.swf\) >](#)
- [iFlex™ Flexible Current Probe \(.swf\) >](#)
- [iFlex™ and Tight Spaces \(.swf\) >](#)
- [iFlex™ and Large Conductors \(.swf\) >](#)
- [iFlex™ and High Current \(.swf\) >](#)

Clamp Meter Resources

- [Where to buy clamp meters >](#)
- [Clamp meter selector tool >](#)
- [Clamp meter application notes and case studies >](#)
- [Clamp meter virtual demos >](#)
- [Clamp meter accessories >](#)
- [Process tools mA clamp meter ROI guide >](#)

It's a tight, tight world.
Starring the Fluke 376 with iFlex™
[Watch now >](#)

Watch the video. Win a prize.

Fluke clamp meters are going mobile

For on-the-go info visit us from any smartphone at:
m.fluke.com

Introducing the Fluke 381 Clamp Meter

The best of both worlds.
[Learn more >](#)

Be ready for anything.
[Learn more >](#)

