



## **Battery Powered Milliohm Meter**

High accuracy, high resolution portable Milliohm Meter
Battery operated for field use

## **Features:**

- · Four terminal Kelvin measurements
- Over-temperature and over-voltage protection
- 5 ranges with 100µ max resolution
- Large 2000 count LCD display
- Auto-Hold and Auto power off
- Invalid test indicators prevent inaccurate measurements
- Built-in water resistant case with shoulder strap
- Complete with 8AA batteries, and 2 sets of test leads (4 wire with 4 alligator clips and 4 wire with 2 Kelvin alligator clips)





Specifications	Range	Resolution	Current	Basic Accuracy
Resistance	200.0m	0.1m	100mA	$\pm (0.5\% \text{rdg} + 2 \text{ digits})$
	2000m	1m	100mA	$\pm (0.5\% \text{rdg} + 2 \text{ digits})$
	20.00	0.01	10mA	$\pm (0.5\% rdg + 2 digits)$
	200.0	0.1	10mA	$\pm (0.5\% \text{rdg} + 2 \text{ digits})$
	2000	1	1mA	$\pm (0.5\% \text{rdg} + 2 \text{ digits})$
Power	8 AA batteries			
Dimensions	9.8 x 7.5 x 4.3" (250 x 190 x 110mm)			
Weight	3.3lbs (1.5kg)			

## **Ordering Information:**

380580......Battery Powered Milliohm Meter 380580-NIST.....380580 with Calibration Traceable to NIST 380565.....Test Leads w/Kelvin clips for 380580



