



## **600W Single Output Laboratory Grade DC Power Supply**

**Dual Action Voltage and Current Control** 

Push knob for fine and coarse tuning

## **Features:**

- 0 to 30V, 20A adjustable output switching mode power supply
- Remote Control for output Voltage/Current and On/Off
- Two user-defined Voltage and Current presets and one 13.8V/20A factory preset
- Automatic Constant Current and Constant Voltage crossover
- Dual 3-Digit LED displays
- High RFI immunity and excellent EMI
- Thermostatic Control Fan from zero to full speed
- Over voltage, over-temperature, and short circuit protection
- Low profile and small footprint
- Complete with power cord



Specifications	Range	
Output Voltage (Res.)	1 to 30V (100mV)	
Output Current (Res.)	1 to 20A (100mA)	
Basic accuracy	±(0.5%+2 digits)	
Load Voltage Regulation	50mV	
Line Voltage Regulation	20mV	
Load Current Regulation	100mA min	
Line Current Regulation	50mA min	
Ripple and Noise	<5mVrms	
Power	382275 - 120VAC, 50Hz/60Hz	
	382276 - 230V, 50Hz/60Hz	
Dimensions	7.9 x 3.5 x 8.5" (200 x 90 x 215mm)	
Weight	5.7lbs (2.6kg)	

## **Ordering Information:**

382275	Laboratory Grade S	Switching Mode Do	C Power Supply	(120V)
382276	Laboratory Grade S	Switching Mode Do	C Power Supply	(230V)



