



### **Precision with Programmable 200 Watt Output DC Power Supply**



**40V/5A programmable supply** With high resolution output and 200 test setup memories

#### **Features:**

- High resolution (1mV and 1mA) user programmable output and two fixed outputs of 5V and 3.3V
- Selectable constant Voltage or Current modes
- Auto output of up to 200 steps with programmable Voltage, Current and time
- Programmable over Voltage protection
- 0 to 60 second programmable overload delay timer
- Storage/Recall memory for 200 test setups
- High stability with low ripple and noise
- Forced air cooling fan
- Bi-directional PC interface commands allow setup and readback using Windows<sup>®</sup> HyperTerminal or similar PC communications programs
- Dual output terminal for source and monitor connections
- Dual high contrast LCD display with backlighting

### **Applications:**

- Precision R & D Voltage and Current source
- Repetitive production tests using setup recall feature
- Prototype board initial power-up with overload protection
- General purpose high power lab requirements



Range	Resolution	Accuracy
0 to 40V	1mV	0.05% ±9mV
0 to 5A	1mA	0.2% ±9mA
5V/2A and 3.3V/3A		
Voltage (mVrms): 3mV		
Current (mArms): 3mA		
110 or 220VAC, 50/60Hz		
12.2 x 9.9 x 5.3" (310 x 250 x 135mm)		
8.4lbs (3.8kg)		
	0 to 40V 0 to 5A 5V/2A and 3.3V/3A Voltage (mVrms): 3mV Current (mArms): 3mA 110 or 220VAC, 50/60Hz 12.2 x 9.9 x 5.3" (310 x 2	0 to 40V 1mV 0 to 5A 1mA 5V/2A and 3.3V/3A Voltage (mVrms): 3mV Current (mArms): 3mA 110 or 220VAC, 50/60Hz 12.2 x 9.9 x 5.3" (310 x 250 x 135mm)

#### **Ordering Information:**

382280 ......40V/5A Precision Programmable DC Power Supply



## 1.800.561.8187



# information@itm.com