

PC CABLE, FOR PC/PG COMMUNICATION WITH SIMOCODE PRO OR SIRIUS 3RW44 SOFT STARTER OR MODULAR SAFETY SYSTEM 3RK3 VIA THE SYSTEM INTERFACE



General technical data:

product brandname	SIRIUS
Product designation	USB PC cable
Design of the product	For connecting to the USB interface of a PC/PG
Ambient temperature	
• during storage	-40 ... +80 °C
• during operation	-25 ... +60 °C
• during transport	-40 ... +80 °C

Certificates/ approvals:

General Product Approval	EMC	Test Certificates		Shipping Approval	
--------------------------	-----	-------------------	--	-------------------	--



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



Shipping Approval	other				
-------------------	-------	--	--	--	--



GL



RMRS

[Confirmation](#)

[PROFINET-Certification](#)

[PROFIsafe-Certification](#)



Profibus

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7941-0AA00-0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7941-0AA00-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF7941-0AA00-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7941-0AA00-0&lang=en



