


## Accessories

### LKSC M2,9x13VZ

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



#### Flexible - More flexible - Profilform

Modular housings in profile form - the flexible modular system comprising coloured and transparent plastic profiles and carrier modules

The combination of standard pitches mounted side by side in any arrangement and metre goods cut accurate to the millimetre creates the perfect balance between flexibility and economic efficiency:

- Pitch profiles with standard widths ranging from 5mm to 45mm allow the mounting of all standard PCB formats.
- Variable heights ensure maximum component density, even with larger electronics components.
- The different installation variations mean that mounting the enclosure directly is as easy as clipping components onto the terminal rail
- Solid hoods protect the module reliably from external influences

The recipe for success: variable profile + modular form components = flexible enclosure concept that offers a large surface area for the PCBs.

The modular concept is designed for modules with high space requirements and suitable for small component quantities and different widths.

#### General ordering data

Type	LKSC M2,9x13VZ
Order No.	<a href="#">4011200000</a>
Version	Accessories, Mounting screw
GTIN (EAN)	4032248415014
Qty.	100 pc(s).

## Data sheet

### Accessories LKSC M2,9x13VZ

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Height	13 mm	Height (inches)	0.512 inch
Net weight	0.647 g		

### System characteristics

Version	Screws	Cross-connection	No
Contact to terminal rail	No	Protection degree	IP20
Encapsulation option	No		

### Material data

Colour code	grey	Colour chart (similar)	RAL 7035
CTI	≥ 600	Storage temperature, min.	-25 °C
Storage temperature, max.	85 °C		

### Classifications

ETIM 3.0	EC000887	ETIM 4.0	EC000887
ETIM 5.0	EC000887	ETIM 6.0	EC002848
UNSPSC	30-21-18-11	eClass 5.1	27-14-11-45
eClass 6.2	27-14-92-14	eClass 7.1	27-14-92-14
eClass 8.1	27-14-92-14	eClass 9.0	27-14-11-92
eClass 9.1	27-14-11-92		

### Notes

Descriptive text technical data .

### Approvals

ROHS Conform

### Downloads

Brochure/Catalogue	<a href="#">CAT 2 PORTFOLIOWEIDMÜLLER EN</a>
Engineering Data	<a href="#">WSCAD</a>
Engineering Data	<a href="#">STEP</a>

**Data sheet**

**Accessories**  
**LKSC M2,9x13VZ**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

