

PRODUCTS

- Rocker switches
- Pushbutton switches
- Toggle switches
- Slide switches**
- Rotary switches
- Foot switches
- Tact and key switches
- Snap-action switches
- Micro-signal switches
- ECO switches
- Sensors
- Systems and modules
- Accessories
- General information
- Catalog request / download

PRODUCTS ▶ SLIDE SWITCHES

Slide switches

SERIES 4021 - DOUBLE AND FOUR-POLE SLIDE SWITCHES - TO 10 A 125 V OR 5 A 250 V AC (AS VOLTAGE SELECTOR SWITCH)


[◀ Show previous product](#)
[Show next product ▶](#)

4021.4620

[Drawing](#)


Similar to original product

[→ Print data sheet](#)

Product number	4021.4620
Actuator color / printing	
Miscellaneous	5 A or 10 A only as voltage selector switch / slide with actuating slot
Switching function	Changeover switch (DPDT)
Number of poles	2-pole
connections	PCB terminal
Mechanical life endurance	1E4
Rating IEC	10 A 250 V AC 1E4
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 40
Ambient temperature	-20 °C ... +80 °C
Ambient temperature	-20 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PA, red
Housing description	PA, black, PA glass fiber-reinforced, natural
Connection surface	external connection silver plated
Contact material	CuSn silver plated
Contact distance	≥ 3 mm
Plug force of the terminals	≤ 60 N
Approval marks	ENEC 15 / cULus
Shop / Stock version	