







































Amp	Volt	Hz	IP Ident. colour + h	Part No.	Panel sockets straight	2 P + $\frac{1}{2}$ IEC/EN 60 309	9	EAN No. 4015609...																														
					flange dimension 75 x 75, fingerproof according to VBG 4																																	
																																						
16	230	50/60	6	411 306																																		
	110	50/60	4	411 304																																		
	400	50/60	9	411 309																																		
32	230	50/60	6	430 306																																		
	110	50/60	4	430 304																																		
	400	50/60	9	430 309																																		
					fixing dimension = a + b, flange dim = d + e																																	
					<table border="1"> <thead> <tr> <th>Ampère</th> <th>a</th> <th>b</th> <th>c</th> <th>d</th> <th>e</th> <th>f</th> <th>h</th> <th>n</th> <th>p</th> </tr> </thead> <tbody> <tr> <td>16 A</td> <td>60</td> <td>60</td> <td>5,5</td> <td>75</td> <td>75</td> <td>52</td> <td>46</td> <td>28</td> <td>6</td> </tr> <tr> <td>32 A</td> <td>60</td> <td>60</td> <td>5,5</td> <td>75</td> <td>75</td> <td>65</td> <td>60</td> <td>27</td> <td>9</td> </tr> </tbody> </table>	Ampère	a	b	c	d	e	f	h	n	p	16 A	60	60	5,5	75	75	52	46	28	6	32 A	60	60	5,5	75	75	65	60	27	9			
Ampère	a	b	c	d	e	f	h	n	p																													
16 A	60	60	5,5	75	75	52	46	28	6																													
32 A	60	60	5,5	75	75	65	60	27	9																													
					10	018734																																
					128	018727																																
					10	018758																																
					10	019564																																
					208	019557																																
					208	019571																																
					flange dimension 107 x 100, fingerproof according to VBG 4																																	
																																						
63	230	50/60	6	460 306																																		
	110	50/60	4	460 304																																		
	400	50/60	9	460 309																																		
125	see page 2/134		6	460 306																																		
			4	460 304																																		
			9	460 309																																		
					fixing dimension = a + b, flange dim = d + e																																	
					<table border="1"> <thead> <tr> <th>Ampère</th> <th>a</th> <th>b</th> <th>c</th> <th>d</th> <th>e</th> <th>f</th> <th>h</th> <th>n</th> <th>p</th> </tr> </thead> <tbody> <tr> <td>63 A</td> <td>85</td> <td>77</td> <td>6,5</td> <td>107</td> <td>100</td> <td>85</td> <td>90</td> <td>52</td> <td>12</td> </tr> </tbody> </table>	Ampère	a	b	c	d	e	f	h	n	p	63 A	85	77	6,5	107	100	85	90	52	12													
Ampère	a	b	c	d	e	f	h	n	p																													
63 A	85	77	6,5	107	100	85	90	52	12																													
					5	020287																																
					586	020270																																
						020294																																
					flange dimension 62 x 62, fingerproof according to VBG 4																																	
																																						
16	230	50/60	6	410 306																																		
	110	50/60	4	410 304																																		
	400	50/60	9	410 309																																		
					fixing dimension = a + b, flange dim = d + e																																	
					<table border="1"> <thead> <tr> <th>Ampère</th> <th>a</th> <th>b</th> <th>c</th> <th>d</th> <th>e</th> <th>f</th> <th>h</th> <th>n</th> <th>p</th> </tr> </thead> <tbody> <tr> <td>16 A</td> <td>47</td> <td>47</td> <td>5,5</td> <td>62</td> <td>62</td> <td>52</td> <td>46</td> <td>28</td> <td>6</td> </tr> </tbody> </table>	Ampère	a	b	c	d	e	f	h	n	p	16 A	47	47	5,5	62	62	52	46	28	6													
Ampère	a	b	c	d	e	f	h	n	p																													
16 A	47	47	5,5	62	62	52	46	28	6																													
					10/60	018376																																
					117	018369																																
						018406																																
					installation in switch cabinets, junction box mountable on DIN-rails, seizes 4,5 MCB module units																																	
																																						
16	230	50/60	6	411 306VS																																		
	110	50/60	4	411 304VS																																		
	400	50/60	9	411 309VS																																		
32	230	50/60	6	430 306VS																																		
	110	50/60	4	430 304VS																																		
	400	50/60	9	430 309VS																																		
					fixing dimension = a + b, flange dim = d + e																																	
					<table border="1"> <thead> <tr> <th>Ampère</th> <th>a</th> <th>b</th> <th>d</th> <th>e</th> <th>f</th> <th>n</th> <th>p</th> </tr> </thead> <tbody> <tr> <td>16 A</td> <td>60</td> <td>60</td> <td>80</td> <td>80</td> <td>56</td> <td>52</td> <td>10</td> </tr> <tr> <td>32 A</td> <td>60</td> <td>60</td> <td>80</td> <td>80</td> <td>62</td> <td>52</td> <td>10</td> </tr> </tbody> </table>	Ampère	a	b	d	e	f	n	p	16 A	60	60	80	80	56	52	10	32 A	60	60	80	80	62	52	10									
Ampère	a	b	d	e	f	n	p																															
16 A	60	60	80	80	56	52	10																															
32 A	60	60	80	80	62	52	10																															
					10	132546																																
					201	160754																																
						160761																																
					10	160969																																
					277	160952																																
						160976																																

Amp	Volt	Hz	IP Ident. colour + h	Part No.	Panel sockets straight	2 P +  IEC/EN 60 309	 	EAN No. 4015609...																																	
16	230	50/60	6	412 306	detachable flange, flange dimension 62 x 62, fingerproof according to VBG 4    	10 129	138067 160907 160914																																		
	110	50/60	4	412 304																																					
	400	50/60	9	412 309																																					
					fixing dimension = a + b, flange dim. = d + e <table border="1"> <thead> <tr> <th>Ampère</th> <th>a</th> <th>b</th> <th>c</th> <th>d</th> <th>e</th> <th>f</th> <th>h</th> <th>n</th> <th>p</th> </tr> </thead> <tbody> <tr> <td>16 A</td> <td>47</td> <td>47</td> <td>5,5</td> <td>62</td> <td>62</td> <td>58</td> <td>50</td> <td>32</td> <td>8,5</td> </tr> </tbody> </table>		Ampère	a	b	c	d	e	f	h	n	p	16 A	47	47	5,5	62	62	58	50	32	8,5															
Ampère	a	b	c	d	e	f	h	n	p																																
16 A	47	47	5,5	62	62	58	50	32	8,5																																
32	230	50/60	6	431 306	detachable flange, flange dimension 80 x 80, fingerproof according to VBG 4    	10 223	019854 137831 161089																																		
	110	50/60	4	431 304																																					
	400	50/60	9	431 309																																					
					fixing dimension = a + b, flange dimension = d + e <table border="1"> <thead> <tr> <th>Ampère</th> <th>a</th> <th>b</th> <th>c</th> <th>d</th> <th>e</th> <th>f</th> <th>h</th> <th>n</th> <th>p</th> </tr> </thead> <tbody> <tr> <td>32 A</td> <td>60</td> <td>60</td> <td>5,5</td> <td>80</td> <td>80</td> <td>60</td> <td>71</td> <td>32</td> <td>8,5</td> </tr> </tbody> </table>		Ampère	a	b	c	d	e	f	h	n	p	32 A	60	60	5,5	80	80	60	71	32	8,5															
Ampère	a	b	c	d	e	f	h	n	p																																
32 A	60	60	5,5	80	80	60	71	32	8,5																																
16	230	50/60	6	415 306	mondo RAL 7035 light grey    	10 200	018895 018888 018901 173730 173747																																		
	110	50/60	4	415 304																																					
	400	50/60	9	415 309																																					
32	230	50/60	6	435 306	   	10 265	019953 019946 019960 173754 173761																																		
	110	50/60	4	435 304																																					
	400	50/60	9	435 309																																					
RW = clear white, RAL 9010 PW = pearl white, RAL 1013					fixing dimension = a + b, flange dimension = d + e <table border="1"> <thead> <tr> <th>Ampère</th> <th>a</th> <th>b</th> <th>c</th> <th>d</th> <th>e</th> <th>f</th> <th>h</th> <th>n</th> <th>r</th> <th>z</th> </tr> </thead> <tbody> <tr> <td>16 A</td> <td>30,4</td> <td>65,2</td> <td>4,1</td> <td>90</td> <td>90</td> <td>38</td> <td>65</td> <td>36</td> <td>96</td> <td>/</td> </tr> <tr> <td>32 A</td> <td>60</td> <td>60</td> <td>4,1</td> <td>90</td> <td>90</td> <td>45</td> <td>75</td> <td>31</td> <td>104</td> <td>80</td> </tr> </tbody> </table>		Ampère	a	b	c	d	e	f	h	n	r	z	16 A	30,4	65,2	4,1	90	90	38	65	36	96	/	32 A	60	60	4,1	90	90	45	75	31	104	80		
Ampère	a	b	c	d	e	f	h	n	r	z																															
16 A	30,4	65,2	4,1	90	90	38	65	36	96	/																															
32 A	60	60	4,1	90	90	45	75	31	104	80																															