

SAFETY ISOLATING TRANSFORMER





POWER : 5VA
 INPUT VOLTAGE : 230V
 FREQUENCY : 50/60Hz
 NOMINAL OUTPUT VOLTAGE : 6V

NON SHORT CIRCUIT PROOF TRANSFORMER
 IP00
 UL94V0

OPERATING TEMPERATURE : -25°C to 50°C
 STORAGE TEMPERATURE : -25°C to 85°C
 INSULATION CLASS (IEC85) : B
 REQUIRED PROTECTION : 800mA FUSE ON SECONDARY

STANDARDS :

- UL506 (File E111078)
- CSA 22-2 (File E111078)
- VDE (File Ref:1398300)
- EN60950 (File Ref:1398300)
- EN61558-1 (File Ref:1398300)
- EN61558-2-6 (File Ref:1398300)
- CE



Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matière:		
	Material:		
Dessiné par: ROUSSEL.Ch	Date: 27/09/2005	Visa: J.P.M.	

Rev	Date	Modification	Dessiné	Visa

DATA SHEET 44229
EI 42x14.8

22 Allée du Clos des Charmes
 Z.A. Les Portes de la Forêt
 77090 COLLEGIEN
 Tel : 01-60-37-55-55
 Fax : 01-60-17-12-00

DS44229