

SAFETY ISOLATING TRANSFORMER





POWER : 10VA
 INPUT VOLTAGE : 230V
 FREQUENCY : 50/60Hz
 NOMINAL OUTPUT VOLTAGE : 24V

NON SHORT CIRCUIT PROOF TRANSFORMER
 IP00
 UL94V0

OPERATING TEMPERATURE : -25°C to 50°C
 STORAGE TEMPERATURE : -25°C to 85°C
 INSULATION CLASS (IEC85) : B
 REQUIRED PROTECTION : 63mA FUSE ON PRIMARY

STANDARDS :

- UL506 (File E111078)
- CSA 22-2 (File E111078)
- VDE (File Ref:1398300)
- EN60950 (File Ref:1398300)
- EN61558-1 (File Ref:1398300)
- EN61558-2-6 (File Ref:1398300)
- CE



| | | | | |
|-----|------|--------------|---------|------|
| Rev | Date | Modification | Dessiné | Visa |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

| | | | |
|-------------------------|------------------|--|----------------|
| Finition: | | Tolérance générale: | |
| Finition: | | General tolerance: | |
| Ech: 1:1 | Matière: | | |
| | Material: | | |
| Dessiné par: ROUSSEL.Ch | Date: 09/02/2003 | Visa: J.P.M. | |
| DATA SHEET 44270 | | | |
| EI 48x16.8 | | | |
| | | 22 Allée du Clos des Charmes Z.A. Les Portes de la Forêt 77090 COLLEGIEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00 | DS44270 |