



Search by part # or keyword

[Products](#)

[Industries & Solutions](#)

[Resources](#)

[TE Store](#)

[Sign In](#)



[Wire And Cable Products](#) > [Twisted Pair Cable](#)

# 44A1121-26-9/96-9

44A1121-26-9/96-9



Raychem

TE Internal #: **383472-000**

TE Internal Description: **44A1121-26-9/96-9**

Alias #: **3-1192875-1**

Cable Type : **Spec 44**

Voltage Rating (VAC): **600**

Insulation Material : **Modified Radiation Cross-linked PVDF**

Conductor Material : **Tin-Coated Copper**

Wire Size (AWG): **26**

[Similar Products](#) | [Digital Datasheet](#)

### Compatible Parts & Tooling

### We are here to help!

Get in touch with our product experts.



[CHAT WITH US](#)



[EMAIL US](#)



[CALL US](#)

Feedback

#### Documents

#### Features

#### Product Compliance

#### Product Drawings

**TWO CONDUCTOR CABLE, RADIATION-CROSSLINKED, POLYALKENE-INSULATED, SHIELDED, JACKETED, LIGHTWEIGHT, GENERAL PURPOSE, 600 VOLT**

tif English

44A1121-26-9/96-9

[Download](#) 44A1121-26-9/96-9 English

**CABLE, RADIATION-CROSSLINKED, POLYALKENE-INSULATED, TWO CONDUCTOR, SHIELDED, JACKETED, LIGHTWEIGHT, GENERAL PURPOSE**

tif English

44A1121-26-9/96-9

[Download](#) 44A1121-26-9/96-9 English

#### Datasheets & Catalog Pages

1654025\_Sec9\_SPEC44

[Download](#) ENG\_CS\_1654025\_Sec9\_SPEC44\_0313.pdf

English

#### Product Specifications

Product Specification

[Download](#) ENG\_SS\_SPEC44\_5.pdf English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.







weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Products with Similar Specs

[View All Similar Products](#)

### THIS PRODUCT

### TOP RESULTS ?

<p>TWISTED PAIR CABLE  <b>44A1121-26-9/96-9</b>            44A1121-26-9/96-9</p>  <p style="text-align: right;"><b>In-Stock</b></p> <p>Cable Type : <b>Spec 44</b>            Voltage Rating : <b>600 VAC</b>            Insulation Material : <b>Modified Radiation Cross-linked PVDF</b>            Conductor Material : <b>Tin-Coated Copper</b>            Wire Size : <b>26 AWG</b></p>	<p>TWISTED PAIR CABLE  <b>44A1121-26-0/9-9</b>            44A1121-26-0/9-9</p>  <p style="text-align: right;"><b>Non-Stocked</b></p> <p>Cable Type : <b>Spec 44</b>            Voltage Rating : <b>600 VAC</b>            Insulation Material : <b>Modified Radiation Cross-linked PVDF</b>            Conductor Material : <b>Tin-Coated Copper</b>            Wire Size : <b>26 AWG</b></p>	<p>TWISTED PAIR CABLE  <b>44A1121-26-0/2-9</b>            44A1121-26-0/2-9</p>  <p style="text-align: right;"><b>Non-Stocked</b></p> <p>Cable Type : <b>Spec 44</b>            Voltage Rating : <b>600 VAC</b>            Insulation Material : <b>Modified Radiation Cross-linked PVDF</b>            Conductor Material : <b>Tin-Coated Copper</b>            Wire Size : <b>26 AWG</b></p>	<p>TWISTED PAIR CABLE  <b>44A1121-26-2/6-9</b>            44A1121-26-2/6-9</p>  <p style="text-align: right;"><b>Non-Stocked</b></p> <p>Cable Type : <b>Spec 44</b>            Voltage Rating : <b>600 VAC</b>            Insulation Material : <b>Modified Radiation Cross-linked PVDF</b>            Conductor Material : <b>Tin-Coated Copper</b>            Wire Size : <b>26 AWG</b></p>
---	--	---	--